

**UFR75120**

Preliminary

FAST RECOVERY EPITAXIAL DIODE**SUPERFAST RECOVERY
RECTIFIER****DESCRIPTION**

The UTC UFR75120 is a superfast recovery rectifier, has half the recovery time of ultrafast diodes.

The UTC UFR75120 is intended for use as a freewheeling/clamping diode and rectifier in a variety of high frequency switching power supplies and other power switching applications. Its low stored charge and hyperfast soft recovery characteristic minimize ringing and electrical noise in many power switching circuits, thus reducing power loss in the switching transistors.

FEATURES



- * Ultrafast soft recovery
- * High reverse voltage capability
- * High junction temperature

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment		Packing
Lead Free	Halogen Free		1	2	
UFR75120L-T472-T	UFR75120G-T472-T	TO-247-2	K	A	Tube

Note: Pin Assignment: A: Anode K: Cathode

UFR75120G-T472-T	(1) Packing Type	(1) T: Tube
	(2) Package Type	(2) T472: TO-247-2
	(3) Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free

MARKING

■ ABSOLUTE MAXIMUM RATINGS (T_A=25°C, unless otherwise specified)

Ratings at 25°C ambient temperature unless otherwise specified. Resistive or inductive load, 60Hz.

PARAMETER		SYMBOL	RATINGS	UNIT
Repetitive Peak Reverse Voltage		V _{RRM}	1200	V
Working Peak Reverse Voltage		V _{RWM}	1200	V
DC Blocking Voltage		V _R	1200	V
Average forward current, δ= 0.5%	T _C =42°C	I _{F(AV)}	75	A
Repetitive peak forward current	Square Wave, 20kHz	I _{FRM}	150	A
Surge non repetitive forward current	Halfwave, 1 Phase, 60Hz	I _{FSM}	500	A
Avalanche Energy		E _{AVL}	50	mJ
Operating Junction Temperature		T _J	-65 ~ +175	°C
Storage Temperature Range		T _{STG}	-65 ~ +175	°C

Note: Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Case	θ _{JC}	0.8	°C/W

■ ELECTRICAL CHARACTERISTICS

(Ratings at 25°C ambient temperature unless otherwise specified. Resistive or inductive load, 60Hz)

PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
Forward voltage drop (Note 1)	V _F	I _F =75A			3.2	V
					2.6	V
Junction to Case (Note 2)	I _R	V _R =V _{RRM}			250	μA
					2	mA
Reverse recovery time	t _{rr}	I _F =1A, dI _F /dt=100A/μs			85	ns

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.