



UF8010

Power MOSFET

80A, 100V N-CHANNEL POWER MOSFET



DESCRIPTION

The UTC **UF8010** uses advanced technology to provide excellent $R_{DS(ON)}$, fast switching speed, low gate charge, and excellent efficiency. This device is suitable for high frequency DC-DC converters, UPS and motor control.

FEATURES

- * $R_{DS(ON)}$:12 m Ω (Typ.)
- * Lower gate-drain charge for lower switching losses
- * Perfect avalanche voltage and current performance
- * Fully characterized capacitance including effective C_{OSS} to simplify design

SYMBOL




ORDERING INFORMATION

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
UF8010L-TA3-T	UF8010G-TA3-T	TO-220	G	D	S	Tube
UF8010L-TF1-T	UF8010G-TF1-T	TO-220F1	G	D	S	Tube
UF8010L-TF2-T	UF8010G-TF2-T	TO-220F2	G	D	S	Tube
UF8010L-TF3-T	UF8010G-TF3-T	TO-220F	G	D	S	Tube
UF8010L-T47-T	UF8010G-T47-T	TO-247	G	D	S	Tube
UF8010L-T2Q-T	UF8010G-T2Q-T	TO-262	G	D	S	Tube
UF8010L-TQ2-T	UF8010G-TQ2-T	TO-263	G	D	S	Tube
UF8010L-TQ2-R	UF8010G-TQ2-R	TO-263	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

UF8010G-TA3-T (1)Packing Type (2)Package Type (3)Green Package		(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF3: TO-220F, TF1: TO-220F1, TF2: TO-220F2, T47: TO-247, T2Q: TO-262 TQ2: TO-263 (3) G: Halogen Free and Lead Free, L: Lead Free
--	--	--

■ MARKING



■ ABSOLUTE MAXIMUM RATINGS ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Gate to Source Voltage		V_{GS}	± 20	V
Continuous Drain Current ($V_{GS}=10\text{V}, T_C=25^{\circ}\text{C}$)		I_D	80 (Note 2)	A
Pulsed Drain Current		I_{DM}	320	A
Avalanche Energy	Single Pulse (Note 2)	E_{AS}	310	mJ
	Repetitive	E_{AR}	26	mJ
Avalanche Current		I_{AR}	45	A
Peak Diode Recovery dv/dt (Note 3)		dv/dt	16	V/ns
Power Dissipation ($T_C=25^{\circ}\text{C}$)	TO-220/TO-262 TO-263	P_D	260	W
	TO-220F/TO-220F1 TO-220F2		54	W
	TO-247		300	W
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ + 150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Starting $T_J = 25^{\circ}\text{C}$, $L = 0.31\text{mH}$, $R_G = 25\Omega$, $I_{AS} = 45\text{A}$.

3. $I_{SD} \leq 45\text{A}$, $di/dt \leq 110\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, $T_J \leq 150^{\circ}\text{C}$

■ THERMAL DATA


PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	TO-220/TO-220F TO-220F1/TO-220F2 TO-262/TO-263 TO-247	θ_{JA}	62.5	$^{\circ}\text{C/W}$
Junction to Case	TO-220/TO-262 TO-263	θ_{JC}	0.57	$^{\circ}\text{C/W}$
	TO-220F/TO-220F1 TO-220F2		2.3	
	TO-247		0.41	

■ ELECTRICAL CHARACTERISTICS (T_J=25°C, unless otherwise specified)


PARAMETER	SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
STATIC CHARACTERISTICS						
Drain-Source Breakdown Voltage	BV _{DSS}	V _{GS} =0 V, I _D =250μA	100			V
Drain-Source Leakage Current	I _{DSS}	V _{DS} =100V, V _{GS} =0V			20	μA
Gate-Source Forward Current	I _{GSS}	V _{GS} = 20 V			200	nA
Gate-Source Reverse Current		V _{GS} = -20 V			-200	nA
ON CHARACTERISTICS						
Gate Threshold Voltage	V _{GS(TH)}	V _{DS} = V _{GS} , I _D = 250μA	2.0		4.0	V
Drain-Source On-State Resistance	R _{DS(ON)}	V _{GS} = 10 V, I _D = 45A (Note 1)		12	15	mΩ
DYNAMIC CHARACTERISTICS						
Input Capacitance	C _{ISS}	V _{DS} =25 V, V _{GS} =0V, f =1.0MHz		3617		pF
Output Capacitance	C _{OSS}			620		pF
Reverse Transfer Capacitance	C _{RSS}			59		pF
SWITCHING CHARACTERISTICS						
Total Gate Charge	Q _G	V _{DS} =80V, V _{GS} =10V I _D = 80A (Note 1)		399	450	nC
Gate-Source Charge	Q _{GS}			41		nC
Gate-Drain Charge	Q _{GD}			96		nC
Turn-On Delay Time	t _{D(ON)}	V _{DS} =30V, I _D = 1A, R _G = 39Ω V _{GS} = 10V (Note 1)		174	200	ns
Rise Time	t _R			370	450	ns
Turn-Off Delay Time	t _{D(OFF)}			757	850	ns
Fall Time	t _F			392	450	ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS						
Maximum Continuous Drain-Source Diode Forward Current	I _S				80	A
Maximum Pulsed Drain-Source Diode Forward Current (Note 1)	I _{SM}				320	A
Drain-Source Diode Forward Voltage	V _{SD}	I _S =80 A , V _{GS} =0 V, T _J = 25°C (Note 1)			1.3	V
Reverse Recovery Time	t _{rr}	I _F =80A, V _{DD} =50V, T _J = 150°C		99	150	ns
Reverse Recovery Charge	Q _{rr}	di/dt = 100 A/μs (Note 1)		460	700	nC

Note: Pulse width ≤ 300μs; duty cycle ≤ 2%.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit




Unclamped Inductive Switching Waveforms

■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.