


**5N50-TC3****Power MOSFET****5A, 500V N-CHANNEL
POWER MOSFET****DESCRIPTION**

The UTC **5N50-TC3** is a high voltage power MOSFET and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and have a high rugged avalanche characteristics. This power MOSFET is usually used at high speed switching applications in power supplies, PWM motor controls, high efficient DC to DC converters and bridge circuits.

FEATURES

* $R_{DS(ON)} \leq 1.75 \Omega$ @ $V_{GS}=10V$, $I_D=2.5A$


* High Switching Speed

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
5N50L-AA3-R	5N50G-AA3-R	SOT-223	G	D	S	Tape Reel
5N50L-TF1-T	5N50G-TF1-T	TO-220F1	G	D	S	Tube
5N50L-TF3-T	5N50G-TF3-T	TO-220F	G	D	S	Tube
5N50L-TM3-T	5N50G-TM3-T	TO-251	G	D	S	Tube
5N50L-TN3-R	5N50G-TN3-R	TO-252	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

6NM70G-AA3-R (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube, R: Tape Reel (2) AA3: SOT-223, TF3: TO-220F, TF1: TO-220F1, TM3: TO-251, TN3: TO-252 (3) G: Halogen Free and Lead Free, L: Lead Free
--	--



MARKING

SOT-223	TO-220F / TO-220F1 TO-251 / TO-252
5N50 Lot Code ← [] [] [] [] [] [] [] [] → Date Code 1 L: Lead Free G: Halogen Free	UTC 5N50 Lot Code ← [] [] [] [] [] [] [] [] → Date Code 1 L: Lead Free G: Halogen Free

■ **ABSOLUTE MAXIMUM RATINGS** ($T_C = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	500	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current	Continuous	I_D	5	A
	Pulsed (Note 2)	I_{DM}	10	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	133	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	3.25	V/ns
Power Dissipation	SOT-223	P_D	5	W
	TO-220F/TO-220F1		31	W
	TO-251/TO-252		52	W
Junction Temperature		T_J	+150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L = 10\text{mH}$, $I_{AS} = 5.15\text{A}$, $V_{DD} = 50\text{V}$, $R_G = 25\ \Omega$ Starting $T_J = 25^\circ\text{C}$

4. $I_{SD} \leq 5.0\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^\circ\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	SOT-223	θ_{JA}	75 (Note)	$^\circ\text{C}/\text{W}$
	TO-220F/TO-220F1		62.5	$^\circ\text{C}/\text{W}$
	TO-251/TO-252		110	$^\circ\text{C}/\text{W}$
Junction to Case	SOT-223	θ_{JC}	25 (Note)	$^\circ\text{C}/\text{W}$
	TO-220F/TO-220F1		4	$^\circ\text{C}/\text{W}$
	TO-251/TO-252		2.4 (Note)	$^\circ\text{C}/\text{W}$

Note: The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.


■ **ELECTRICAL CHARACTERISTICS** ($T_J = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	V _{GS} =0V, I _D = 250μA	500			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} =500V, V _{GS} =0V			10	μA
Gate-Source Leakage Current	Forward	I _{GSS}	V _{GS} =30V, V _{DS} =0V			100	nA
	Reverse		V _{GS} =-30V, V _{DS} =0V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2.0		4.0	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =10V, I _D =2.5A			1.75	Ω
DYNAMIC CHARACTERISTICS							
Input Capacitance		C _{ISS}	V _{GS} =0V, V _{DS} =25V, f=1.0 MHz		438		pF
Output Capacitance		C _{OSS}			61		pF
Reverse Transfer Capacitance		C _{RSS}			4.6		pF
SWITCHING CHARACTERISTICS							
Total Gate Charge (Note 1)		Q _G	V _{DS} =100V, V _{GS} =10V, I _D =5.0A I _G =1mA (Note 1, 2)		13		nC
Gateource Charge		Q _{GS}			5.5		nC
Gate-Drain Charge		Q _{GD}			2		nC
Turn-on Delay Time (Note 1)		t _{D(ON)}	V _{DS} =100V, V _{GS} =10V, I _D =5.0A, R _G =25Ω (Note 1, 2)		7		ns
Rise Time		t _R			18		ns
Turn-off Delay Time		t _{D(OFF)}			32		ns
Fall-Time		t _F			20		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I _S				5	A
Maximum Body-Diode Pulsed Current		I _{SM}				10	A
Drain-Source Diode Forward Voltage (Note 1)		V _{SD}	V _{GS} =0V, I _S =5.0A			1.4	V
Reverse Recovery Time (Note 1)		t _{rr}	V _{GS} =0V, I _S =5.0A,		250		ns
Reverse Recovery Charge		Q _{rr}	dl _F /dt=100A/μs (Note1)		1.78		μC


Notes: 1. Pulse Test : Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.