

A	Dept	1	2	3	4	5	6	7	8	A
	Qty	1								
	DC	1								
	ED	1								
	IE	1								
B	ISO	1								B
	PD	1								
	R&D	1								
	SD	1								
	QA	1								
C	QC	1								C
	QE	1								
D										D
E										E
F										F
G										G
H										H

NOTES:

1. SPECIFICATIONS

- Contact Rating: 100mA at 30Vdc
- Insulation Resistance:100MΩ min.
- Contact Resistance:100mΩ max.
- Dielectric Withstanding Voltage: 250V AC(rms) for 1 minute.
- Operating Life:10,000 cycles
- Travel:1.5±0.3mm
- Operation Temperature Range: -25°C to +70°C

2. PRODUCT NUMBER CODE:

DS1041-07 - X X X X X X X

- Operating Life 1: 10,000 cycles
- Lock Support X: W/O Lock Type
- Operating force 200: 200gf
- Packing type A: polybag
- Actuator color V: Ivory
- Housing color K: Black
- Profile Height 075:7.5mm
- No. of contacts 4: 4 pos

CIRCUIT DIAGRAM

RECOMMEND P.C.B LAYOUT

Tolerance±0.05

GENERAL TOLERANCE

X.	±0.60	X.	±5°
.X	±0.38	.X	±3°
.XX	±0.25	.XX	±2°

ANGLE TOLERANCE

DRAWING TYPE	CUSTOMER
SCALE	1:1 SHEET 1 OF 1
DRAWING NO.	C-DS1041-07-XXXXXXXX-A

PROJECTION

UNITS mm

SHEET SIZE A4

TITLE 6.0*6.0*7.5mm W/O Lock Switch 4P DIP Type

SERIES DS1041-07 SERIES

晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD