



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: ttsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 1680 MHz SMD 3.0X3.0 mm

TST Part No.: TA1078B

Customer Part No.: _____

Customer signature required
Company: _____
Division: _____
Approved by : _____
Date: _____

Checked by: _____ Bob Chau 

Approved by: _____ Francis Chen 

Date: _____ 5, 24, 2010

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com

Web: www.taisaw.com

SAW Filter 1680 MHz

MODEL NO.:TA1078B

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -50°C to +95°C

RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:

Terminating source impedance (balanced) :


$Z_s = 200 \ \Omega \ // \ 18nH$

Terminating load impedance (single ended) :

$Z_L = 50 \ \Omega$

Item	Unit	Min.	Typ.	Max.	Note
Center Frequency Fc	MHz	-	1680	-	-
Bandwidth at -1.5 dB	MHz	27	76	-	-
Insertion Loss in 1666.5~1693.5 MHz	dB	-	2.6	5	-
Amplitude ripple (1666.5 MHz ~ 1693.5 MHz)	dB	-	0.4	1.5	-
I/O VSWR (1666.5 MHz ~ 1693.5 MHz)		-	1.7	2.5	-
Attenuation (reference level from 0 dB)					
50 ~ 1580 MHz	dB	42	60	-	-
1800 ~ 3000 MHz	dB	42	49	-	-
3000 ~ 4000 MHz	dB	35	43	-	-
4000 ~ 6000 MHz	dB	18	30	-	-


C.OUTLINE DRAWING:




△ : Year Code (2009->9, 2010->0, ..., 2018->8)

□ : Date Code (W01->A,...W26->Z,...W52->z)



D. MEASUREMENT CIRCUIT:



E. PCB Footprint:




F. Frequency Characteristics :




Reflection Functions :

S11




S22




G. PACKING:

1. REEL DIMENSION

(Reel Count : 7''=1000 ; 13''=3000)



2.TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

