



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 153.6MHz SMD 5.0×7.0mm

TST Part No.: TB0782A

Customer Part No.: _____


Customer signature required


Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Ricky Lee 

Approved by: _____ Francis Chen 

Date: _____ 2009/07/29

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

IF SAW Filter 153.6MHz(BW=10MHz) SMD 5X7mm

MODEL NO.: TB0782A

REV.1.0

A. MAXIMUM RATING:

1. Operating Temperature: 0 °C ~ +70 °C
2. Storage Temperature: -40 °C ~ +85 °C
3. Input power: 10dBm

RoHS Compliant
Lead free
Lead-free soldering

B. Characteristics :

Ambient Temperature: 25 °C

Characteristics		Value			Note
		Min.	Typ.	Max.	
Center frequency F_c	MHz	-	153.6	-	-
Minimum Insertion loss I.L.	dB	-	10.0	13.0	-
1dB BW	MHz	10	12.3	-	-
Passband Ripple ($F_c \pm 5.0\text{MHz}$)	dB	-	0.6	1.0	-
Attenuation (Reference to Minimum Insertion loss)					
141.1MHz	dB	10	50	-	-
166.1MHz	dB	10	47	-	-
Temp Coefficient	ppm/K	-	-23	-	-
Matching:					
1.The input of the filter will be matched to <u>50 ohm</u>					
2.The output of the filter will be matched to <u>50 ohm</u>					

C. Frequency Characteristics :

1. S21 Response: (span : 50MHz)




Fig1. Horizontal: 5MHz/Div Vertical: 10dB/Div

2. Group-Delay Ripple: (span : 20MHz)






Fig2. Horizontal: 2MHz/Div Vertical: 100nec/Div


3. S11 Smith Chart: (span : 50MHz)



4. S22 Smith Chart (span : 50MHz)




D. Measurement Circuit:



Zin and Zout are 50Ω .

$L1=74.8\text{nH}$, $C1=47\text{pF}$, $L2=78\text{nH}$, $C2=33\text{pF}$

E. Outline Drawing:



Pin J: RF input

Pin D: RF output

Pin K,E: Case Ground

Pin A, B, C, F, G, H: Ground


□ : Week Code (W01->A,W02->B,...W27->a,...,W52->z)

Unit : mm

△ : Product / Year Code

Year	2005 2009	2006 2010	2007 2011	2008 2012
Product Code	B	b	<u>B</u>	<u>b</u>


F. PCB Footprint:



Unit: mm


H. PACKING:

1. REEL DIMENSION



Unit: mm

2. TAPE DIMENSION



Unit: mm

I. RECOMMENDED REFLOW PROFILE_ :

