



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: 114MHz 0.1MHz BW SMD 9.1X7.1mm IF SAW Filter

TST Parts No.: TB1172A

Customer Parts No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Kazuma Lee 

Approval by: _____ Bob Chau 

Date: _____ 11 / 13 / 2014

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

IF SAW Filter 114MHz(BW=100KHz) SMD 9.1X7.1mm

MODEL NO.: TB1172A

REV. NO.1

A. MAXIMUM RATING:

1. Operating temperature range: -40°C to 85°C
2. Storage temperature range: -40°C to 85°C
3. Input Power Level : 10 dBm
4. Maximum DC Voltage : 10V

RoHS Compliant
Lead free
Lead-free soldering

Electrostatic Sensitive Device

B. Characteristics :

1. Ambient Temperature: 25 °C

Characteristics	Value			Note
	Min.	Typ.	Max.	
Center frequency FC MHz	-	114	-	-
Minimum Insertion loss I.L. dB	-	6.8	9.0	-
1dB Bandwidth KHz	-	151	-	-
3dB Bandwidth KHz	100	249	-	-
Passband Ripple Fc ± 50KHz dB	-	0.8	3.0	-
Attenuation (Reference level from minimum Insertion loss)				
Fc-1MHz dB	20	47	-	-
Fc+1MHz dB	20	46	-	-
Temp Coefficient ppm/K ²	-	-0.036	-	-

C. Frequency Characteristics :

1. S21 Response




Fig1. Horizontal: 0.2MHz/Div Vertical: 10dB/Div

2. Pass band Response and Group Delay Response:






Fig2. Horizontal: 0.05MHz/Div Vertical: 1dB/Div
Vertical: 100ns/Div

1. Smith Chart:




D. Outline Drawing:



L1=220nH L2=180nH +18nH C1=30pF C2=39pF

E. Outline Drawing:



Pin h: RF Input

Pin c: RF Output

Pin a, b, d, e, f, g, j, k : To be ground

Unit : mm

□ : Week Code


△ : Product / Year Code

Year	2013 2017	2014 2018	2015 2019	2016 2020
Product Code	B	b	<u>B</u>	<u>b</u>

Week Code Table


WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

F. PCB Footprint:




G. PACKING:

1. REEL DIMENSION (Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE:

