



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: 70MHz 0.78MHz BW SMD 13.3X6.5 mm SAW IF Filter

TST Part No.: TB1339A

Customer Part No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Kazuma Lee

Approved by: _____ Andy Yuu

Date: _____ 05 / 24 / 2019

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 70MHz 0.78MHz BW (SMD 13.3×6.5 mm)

MODEL NO.: TB1339A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC voltage: 5 V
3. Operating Temperature: -40 °C to +85 °C
4. Storage Temperature: -40 °C to +85 °C
5. Moisture Sensitivity Level: MSL1

RoHS Compliant
Lead free
Lead-free soldering



Electrostatic Sensitive Device

B. ELECTRICAL CHARACTERISTICS:


Specification at room temperature 25 °C

Item	Unit	Min.	Typ.	Max.
Center Frequency (fo)	MHz	-	70.0	-
Insertion Loss	dB	-	10.5	12.5
1dB Bandwidth	MHz	-	0.78	-
3dB Bandwidth	MHz	1.0	1.22	-
40dB Bandwidth	MHz	-	3.2	4.0
Amplitude Ripple (fo ± 0.35 MHz)	dB	-	0.9	1.5
Group Delay Variation (fo ± 0.35 MHz)	nsec	-	120	250
Absolute Delay	usec	-	0.92	-
Attenuation (reference level from IL _{fo})				
Ultimate Rejection	dB	37	42	-
Temperature Coefficient of Frequency	ppm/°C	-	-18	-

C. FREQUENCY CHARACTERISTICS:




D. MATCHING CIRCUIT:



$$C1 = C2 = 75\text{pF}, L1 = L2 = 100\text{nH}$$

E. OUTLINE DRAWING:



#L: Input

#E: Output

Others: Ground

□: Week Code

Unit: mm

△: Product / Year Code


Product / Year Code

Year	2017 2021	2018 2022	2019 2023	2020 2024
Product Code	B	b	<u>B</u>	<u>b</u>

Week Code Table

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

F. PCB FOOTPRINT:




Unit: mm

G. PACKING:

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)



1. Preheating shall be fixed at 150~180℃ for 60~90 seconds.
2. Ascending time to preheating temperature 150℃ shall be 30 seconds min.
3. Heating shall be fixed at 220℃ for 50~80 seconds and at 260℃+0/-5℃ peak (20~40sec).
4. Time: 2 times.

