








N=NUMBER OF POLES

Dim L	N×10.16
Dim B	(N-1)×10.16

	TOL	
	2P-6P	7P-12P
Dim L	±0.25	±0.40
Dim B	±0.25	±0.40

SIGN	DATE	DESCRIPTION	APPROVER
△	04/01'09	How to order is changed From xx66x0xxxxG to xx62x0xxxxG	Jacke
△	09/16'09	Voltage rating is changed From 300V to 600V	Aaron
△	09/16'09	Current rating is changed From 57A to 64A	Aaron
△	09/16'09	Torque is changed From 10.4 LB-In to 19 LB-In	Aaron
△	09/16'09	Wire guard solder pin is changed From Brass to Copper	Aaron
△	01/19'10	Add is cULus	Aaron
△	09/17'10	Construction is change	Aaron
△	06/02'11	Voltage rating is changed From 600V to 300V	Steven

Material:

- Item① Terminal housing: Thermoplastic (UL 94V-0)
- Item② Terminal cover: Thermoplastic (UL 94V-0)
- Item③ Clamp: Zinc alloy . Ni plated
- △ ● Item④ Wire guard solder pin: Copper .Tin plated
- Item⑤ Terminal screw: Steel Zinc plating“+/-”slot type

- Electrical cULus
- △ ● Voltage rating : 300V
 - △ ● Current rating : 64A
 - Wire range :
 - Solid wire (AWG) : 6-22
 - Stranded wire (AWG) : 6-22
 - △ ● Torque (LB-In.) : 19
 - Screw : M4.5
 - Wire strip length : 11-12mm
 - Withstanding voltage : 1.6KV
 - Operating temperature : -40°C+115°C
 - Soldering temperature : 250°C+10°C/5 Sec
 - △ ● Safety Approval: cULus
 - Critical dimension:

△ KQ xx 6 2 x 1 xxxx G

No. of poles end stackable design	0 Black (RAL9005)	0000:"@Logo (Standard)
02 2 CONTACTS	2 Red (RAL3001/D)	000A:"ANYTEK"Logo
03 3 CONTACTS	3 Orange(RAL2011/P)	Any special item by customer request,
... ..	4 Yellow(RAL1018/A)	please contact sales department.
12 12 CONTACTS	5 Green(RAL6018/T)	
	6 Blue (RAL5015/A)	
	8 Grey(RAL7035/D)	

RoHS
Pb<40,000ppm

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	KQ 10.16 Series contact 1.00x1.00mm---B Type					
PART NO.	KQxx62x1xxxx G			DWG NO.	8KQ0002	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance	
		STEVEN 2011.06.02	Aaron 2009.09.16		UNIT: mm	X. ±0.50
					SCALE: NONE	X.X ±0.30
					SHEET: 01/01	X.XX ±0.10
					REV.: G	X° ±1°