



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 1602 MHz SMD 3.0X3.0 mm

TST Part No.: TA1036A

Customer Part No.: _____


Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Bob Chau 

Approved by: _____ Francis Chen 

Date: _____ 5, 13, 2010

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: ttsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 1602 MHz

MODEL NO.:TA1036A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -50°C to +95°C

RoHS Compliant
Lead free
Lead-free soldering


B. ELECTRICAL CHARACTERISTICS:

Terminating source impedance (differential) : $Z_s = 200 \Omega // 18nH$

Terminating load impedance (differential) : $Z_L = 200 \Omega // 18nH$

Item	Unit	Min.	Typ.	Max.	Note
Center Frequency Fc	MHz	-	1602	-	-
Bandwidth at -3 dB	MHz	-	61	-	-
Insertion Loss in 1596~1607 MHz	dB	-	3	4	-
Amplitude ripple (1596 MHz ~ 1607 MHz)	dB	-	0.6	2	-
Group delay variation (1596MHz ~ 1607MHz)	ns	-	6	15	-
I/O Return Loss (1596 MHz ~ 1607 MHz)	dB	8	9	-	-
Attenuation (reference level from 0 dB)					
10 ~ 1500 MHz	dB	45	48	-	-
1700 ~ 2400 MHz	dB	43	50	-	-


C.OUTLINE DRAWING:




△ : Year Code (2006->6, ..., 2009->9)

□ : Date Code (W01->A,...W26->Z,...W52->z)



D. MEASUREMENT CIRCUIT:




E. PCB Footprint:



F. Frequency Characteristics :






Reflection Functions :

S11




S22




G. PACKING:

1. REEL DIMENSION

(Reel Count : 7''=1000 ; 13''=3000)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

