

A	Dept						
	Qty						
	DC	1					
	ED	1					
	IE	1					
	ISO	1					
	PD	1					
	R&D	1					
B	SD	1					
	QA	1					
	QC	1					
	QE	1					
C							
D							
E							
F							
G							
H							

NOTES:

1. SPECIFICATIONS

- Contact Rating: 100mA at 30Vdc
- Insulation Resistance:100MΩ min.
- Contact Resistance:100mΩ max.
- Dielectric Withstanding Voltage: 250V AC(rms) for 1 minute.
- Operating Life:10,000 cycles
- Travel:1.5±0.3mm
- Operation Temperature Range: -25°C to +70°C

REV. DESCRIPTION DRAWN CHECKED APPROVED

A	NEW RELEASE	JLZ 08/08/18'		

Wave Soldering: Recommended Solder Temperature At 500°f(260°C)max. 5 Seconds

Hand Soldering: Use Soldering Iron Of 30 Watts,Controlled At 608°f(320°C)Approximately 2 Seconds.

2. PRODUCT NUMBER CODE:

DS1041-08 - X X X X X X X

- Operating Life 1: 10,000 cycles
- Lock Support S: W/ Lock Type
- Operating force 200: 200gf
- Packing type A: polybag
- Actuator color K: Black
- Housing color K: Black
- Profile Height 140:14mm 175:17.5mm 220:22mm
- No. of contacts 6: 6 pos

S

H

8.50

3.50

0.5

2.50

2.50

5.00

6-Ø1.00

5.50

CIRCUIT DIAGRAM

RECOMMEND P.C.B LAYOUT

Tolerance±0.05

GENERAL TOLERANCE

X.	±0.60
.X	±0.38
.XX	±0.25

ANGLE TOLERANCE

X.	±5°
.X	±3°
.XX	±2°

DRAWING TYPE CUSTOMER

SCALE 1:1 SHEET 1 OF 1

DRAWING NO. C-DS1041-08-XXXXXXX-A

PROJECTION

UNITS mm

SHEET SIZE A4

TITLE 8.5*8.5mm W/ Lock Switch 6P DIP Type

SERIES DS1041-08 SERIES

晨翔电子有限公司

CONNFLY CONNFLY ELECTRONIC CO. LTD