







P.C.B LAYOUT



N = Number of poles

Dim A=Nx2.5+1.5

Dim B=(N-1)x2.5

Poles	Dim A	Dim B
2-6p	±0.20	±0.20
7-12p	±0.25	±0.25
13-24p	±0.30	±0.30

Version	SIGN	DATE	DESCRIPTION	APPROVER
C	△	2009.6.18	The design is changed	Jacke
D	△	2009.10.07	The design is changed	Jacke
D	△	2009.10.07	The dimension is changed from 16.2mm to 16.0mm	Jacke
D	△	2009.10.07	Add UL standard	Jacke
E	△	2011.01.12	Structure changed	Runner
F	△	2017.01.20	Change the pole's numerical range of the tolerance table.	Eddie

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item a: Terminal lever: Thermoplastic (UL94 V-0)
- Item b: Terminal body: Thermoplastic (UL94 V-0)
- Item c: Solder pin: Brass Tin plated
- Item d: wire guard: Stainless steel
- Item e: Terminal cover: Thermoplastic (UL94 V-0)

Electrical

cULus

- Voltage rating: 150V
- Current rating: 3A
- Wire range: 0.08 ~ 0.52mm²
- Solid wire(AWG): 20-28
- Stranded wire(AWG): 20-28
- Wire strip length: 9-10mm
- Withstanding Voltage: 1.3KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C
- Safety Approval: cULus
- Critical dimension: △

No. OF POLES	NA xx B 0 x 0 xxxx G	RoHS compliant (lead<4%) In copper Alloy
02 2 poles	△ COLOR	0000: "@" Logo (Standard)
03 3 poles	0 Black (RAL9005)	000A: "ANYTEK" Mark
...	2 Red (RAL3001/D)	Any special item by customer request.
24 24 poles	3 Orange (RAL2011/P)	please contact sales department.
	4 Yellow (RAL1018/A)	
	5 Green (RAL6018/T)	
	6 Blue (RAL5015/A)	
	8 Grey (RAL7004/p)	
	C Multiple colors	





Amphenol
ANYTEK

CUSTOMER COPY


ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR, PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	NA 2.5mm series Double tail A type Vertical (90D wire inlet)			
PART NO.	NAxxB0x0xxxxG		DWG NO.	8NA0001
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.
14/12/17	Runner	2011.01.12	Jacke	2009.10.07
SHEET: 01/01				REV: F
UNIT: mm				Tolerance
SCALE: 4/1				X ±0.50
				X.X ±0.30
				X.XX ±0.10
				X° ±1°



P.C.B LAYOUT
Top view


The color of lever is consistent with body's




SECTION P-P

N = Number of poles
Dim A = $N \times 2.5 + 1.5$
Dim B = $(N - 1) \times 2.5$

	Dim A	Dim B
3-5p	± 0.20	± 0.20
7-11p	± 0.25	± 0.25
13-23p	± 0.30	± 0.30



Left contacts pin omit
Right side with cover



SIGN	DATE	DESCRIPTION	APPROVER
△	01/07'09	P.C.B LAYOUT changed	Jacke
△	2009.6.18	The design is changed	Jacke
△	2009.10.07	The design is changed	Jacke
△	2009.10.07	The dimension is changed from 16.2mm to 16.0mm	Jacke
△	2009.10.07	Add UL standard	Jacke
△	2011.01.12	Structure changed	Runner
△	04/04'11	Add is spec.	Chen Bo
△	12/28'13	update the drawing	Da cheng

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item a : Terminal lever: Thermoplastic (UL94 V-0)
- Item b : Terminal Normal housing: Thermoplastic (UL94 V-0)
- Item c : Terminal side body Thermoplastic (UL94 V-0)
- Item d : Terminal cover: Thermoplastic (UL94 V-0)
- Item e : Left contacts pin omit Right side: Brass Tin plated
- Item f : Right contacts pin omit Left side: Brass Tin plated
- Item g : wire guard: Stainless steel

Electrical cULus

- Voltage rating: 150V
- Current rating: 3A
- Wire range: 0.08 0.52mm²
- Solid wire(AWG): 20-28
- Stranded wire(AWG): 20-28
- Wire strip length: 9-10mm
- Withstanding Voltage: 1.3KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C±5°C/5 Sec
- Safety Approval: cULus
- Critical dimension: ∇

NA xx B 0 x 1 xxxx G

NO of poles
03 3 poles
05 5 poles
...
23 23 poles

- Body Color
- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7004/P)
- 9 White(RAL1102)
- C Multiple colors

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request, please contact sales department.





ANYTEK

CUSTOMER COPY


ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		NA 2.5mm series Single tail B type Vertical (90D wire inlet) 車數P					
PART NO.		NAXxB0x1xxxxG		DWG NO.		8NA0003	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.		Tolerance	
		Da cheng	Da cheng			UNIT: mm	X. ±0.50
		2013.12.28	2013.12.28			SCALE: 4/1	X.X ±0.30
						REV: F	X.XX ±0.10
				SHEET: 01/01			X° ±1°




P.C.B LAYOUT
Top view


The color of lever is consistent with body's



SECTION P-P



Left contacts pin omit
Right side with cover



N = Number of poles
Dim A = $N \times 2.5 + 1.5$
Dim B = $(N - 1) \times 2.5$

	Dim A	Dim B
2-6p	± 0.20	± 0.20
8-12p	± 0.25	± 0.25
14-24p	± 0.30	± 0.30

SIGN	DATE	DESCRIPTION	APPROVER
△			
△			
△			
△			
△			

THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item a: Terminal lever: Thermoplastic (UL94 V-0)
- Item b: Terminal Normal housing: Thermoplastic (UL94 V-0)
- Item c: Terminal side body: Thermoplastic (UL94 V-0)
- Item d: Terminal cover: Thermoplastic (UL94 V-0)
- Item e: Left contacts pin omit Right side: Brass Tin plated
- Item f: Right contacts pin omit Left side: Brass Tin plated
- Item g: wire guard: Stainless steel

Electrical

cULus

- Voltage rating: 150V
- Current rating: 3A
- Wire range: 0.08 ~ 0.52mm²
- Solid wire(AWG): 20-28
- Stranded wire(AWG): 20-28
- Wire strip length: 9-10mm
- Withstanding Voltage: 1.3KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 260°C ± 5°C / 5 Sec
- Safety Approval: cULus
- Critical dimension: ▽

NA xx B 0 x 1 xxxx G

- NO of poles
- 02 2 poles
 - 04 4 poles
 -
 - 24 24 poles

- Body Color
- 0 Black (RAL9005)
 - 2 Red (RAL3001/D)
 - 3 Orange (RAL2011/P)
 - 4 Yellow (RAL1018/A)
 - 5 Green (RAL6018/T)
 - 6 Blue (RAL5015/A)
 - 8 Grey (RAL7004/P)
 - 9 White (RAL1102)
 - C Multiple colors

0000: "@" Logo (Standard)
000A: "ANYTEK" Mark
Any special item by customer request, please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		NA 2.5mm series Single tail B type Vertical (90D wire inlet) 雙線P			
PART NO.	NAxxB0x1xxxxG			DWG NO.	BNA0008
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	
		Da cheng 2013.12.28	Da cheng 2013.12.28		
SHEET: 01/01				UNIT: mm	Tolerance
				SCALE: 4/1	X. ±0.50
				REV: B	X.X ±0.30
					X.XX ±0.10
					X* ±1°