


**10N50K-MT****Power MOSFET****10A, 500V N-CHANNEL
POWER MOSFET****DESCRIPTION**

The UTC **10N50K-MT** is an N-channel mode power MOSFET using UTC's advanced technology to provide customers with planar stripe and DMOS technology. This technology allows a minimum on-state resistance and superior switching performance. It also can withstand high energy pulse in the avalanche and commutation mode.

The UTC **10N50K-MT** is generally applied in high efficiency switch mode power supplies, active power factor correction and electronic lamp ballasts based on half bridge topology.

FEATURES


- * $R_{DS(ON)} \leq 0.68\Omega$ @ $V_{GS}=10V$, $I_D=5.0A$
- * High Switching Speed
- * 100% Avalanche Tested

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
10N50KL-TF1-T	10N50KG-TF1-T	TO-220F1	G	D	S	Tube
10N50KL-TF2-T	10N50KG-TF2-T	TO-220F2	G	D	S	Tube
10N50KL-TF3-T	10N50KG-TF3-T	TO-220F	G	D	S	Tube

Note: Pin Assignment: G: Gate D: Drain S: Source

	(1) T: Tube (2) TF1: TO-220F1, TF2: TO-220F2, TF3: TO-220F (3) G: Halogen Free and Lead Free, L: Lead Free
--	---

MARKING

■ ABSOLUTE MAXIMUM RATINGS (T_C=25°C, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V _{DSS}	500	V
Gate-Source Voltage		V _{GSS}	±30	V
Drain Current	Continuous (T _C =25°C)	I _D	10 (Note 2)	A
	Pulsed (Note 3)	I _{DM}	20 (Note 2)	A
Avalanche Current (Note 3)		I _{AR}	10	A
Avalanche Energy	Single Pulsed (Note 4)	E _{AS}	245	mJ
Peak Diode Recovery dv/dt (Note 5)		dv/dt	4.5	V/ns
Power Dissipation		P _D	48	W
Derate above 25°C			0.38	W/°C
Junction Temperature		T _J	+150	°C
Storage Temperature		T _{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Drain current limited by maximum junction temperature.

3. Repetitive Rating: Pulse width limited by maximum junction temperature.

4. L = 10mH, I_{AS} = 7A, V_{DD} = 50V, R_G = 25Ω, Starting T_J = 25°C

5. I_{SD} ≤ 10A, di/dt ≤ 200A/μs, V_{DD} ≤ BV_{DSS}, Starting T_J = 25°C

■ THERMAL DATA

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ _{JA}	62.5	°C/W
Junction to Case	θ _{JC}	2.58	°C/W


■ **ELECTRICAL CHARACTERISTICS** ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV_{DSS}	$I_D=250\mu A, V_{GS}=0V$	500			V
Drain-Source Leakage Current		I_{DSS}	$V_{DS}=500V, V_{GS}=0V$			10	μA
Gate- Source Leakage Current	Forward	I_{GSS}	$V_{GS}=+30V, V_{DS}=0V$			+100	nA
	Reverse		$V_{GS}=-30V, V_{DS}=0V$			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		$V_{GS(TH)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	2.0		4.0	V
Static Drain-Source On-State Resistance		$R_{DS(ON)}$	$V_{GS}=10V, I_D=5.0A$			0.68	Ω
DYNAMIC PARAMETERS							
Input Capacitance		C_{ISS}	$V_{GS}=0V, V_{DS}=25V, f=1.0MHz$		1322		pF
Output Capacitance		C_{OSS}			140		pF
Reverse Transfer Capacitance		C_{RSS}			7.5		pF
SWITCHING PARAMETERS							
Total Gate Charge		Q_G	$V_{DS}=100V, V_{GS}=10V, I_D=10A, I_G=1mA$		35		nC
Gate to Source Charge		Q_{GS}			7.6		nC
Gate to Drain Charge		Q_{GD}			4		nC
Turn-ON Delay Time		$t_{D(ON)}$	$V_{DD}=100V, V_{GS}=10V, I_D=10A, R_G=25\Omega$		16.8		ns
Rise Time		t_R			82		ns
Turn-OFF Delay Time		$t_{D(OFF)}$			58.2		ns
Fall-Time		t_F			19.6		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I_S				10	A
Maximum Body-Diode Pulsed Current		I_{SM}				20	A
Drain-Source Diode Forward Voltage		V_{SD}	$I_S=10A, V_{GS}=0V$			1.4	V
Body Diode Reverse Recovery Time		t_{rr}	$I_S=10A, V_{GS}=0V,$		352		nS
Body Diode Reverse Recovery Charge		Q_{rr}	$dI_F/dt=100A/\mu s$		4.4		μC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS









Peak Diode Recovery dv/dt Test Circuit & Waveforms









Peak Diode Recovery dv/dt Waveforms







■ TEST CIRCUITS AND WAVEFORMS




■ TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.