

SIGN	DATE	DESCRIPTION	APPROVER
Δ	9/17/10	How to older is changed	Runner
Δ	05/27/11	Voltage rating is changed from 160 V to 300 V	Steven
Δ	05/27/11	Withstanding Voltage is changed from 1.32 Kv to 1.6 Kv	Steven
Δ	05/27/11	Add "cullus" Safety Approval logo	Steven



THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!

Material:

- Item ① Terminal housing: PA66 30% GF (UL94V-0)
- Item ② Contact pin of short: Copper Tin plated
- Item ③ Contact pin of long: Copper Tin plated

Electrical:

- Δ ● Voltage rating: 300V
- Current rating: 5.5A
- Δ ● Withstanding Voltage: 1.6 KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C ±10°C/5 Sec
- Δ ● Safety Approval: 
- Critical dimension: 



PCB Layout

DIMENSION

Dim.L	(N/2-1) × 3.81+4.4
Dim.P	(N/2-1) × 3.81

N = Number of poles

	TOL		
	2×2P-2×5P	2×6P-2×16P	2×17P-2×24P
Dim.L	±0.20	±0.30	±0.40
Dim.P	±0.15	±0.25	±0.30

KE XX 3 3 X 1 XXXX G

No. OF POLES — G: Pb<4,0000ppm

04: 2×2 POLES
06: 2×3 POLES

48: 2×24 POLES

COLOR

- 0 Black (RAL9005)
- 2 Red (RAL3001/D)
- 3 Orange(RAL2011/P)
- 4 Yellow(RAL1018/A)
- 5 Green(RAL6018/T)
- 6 Blue (RAL5015/A)
- 8 Grey(RAL7035/D)

Δ A00 0: "@" Mark
A00 A: "ANYTEK" Mark

Any special item by customer request. please contact sales department.

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE		KE 3.81mm With Latch holder Series (Right angle) DIP type	
PART NO.	KExx33x1xxxxG	DWG NO.	8KE0308
APPROVED	CHECKED	DESIGNED	DRAWN
	Steven	2011.05.27	Runner
	2010.04.12		
SHEET: 01/01		REV.: D	

X.	±0.50
X.X	±0.30
X.XX	±0.10
X°	±1°