



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Name: 165.74 MHz 27MHz BW SMD 7.0 x 5.0 mm SAW IF Filter

TST Parts No.: TB1037A

Customer Parts No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Kazuma Lee

Approval by: _____ Francis Chen

Date: _____ 11 / 08 / 2011

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No.3, Industrial 2nd Rd., Ping-Chen Industrial District, Taoyuan, Taiwan, R.O.C.

TEL: 886-3-4690038

FAX: 886-3-4697532

E-mail: tstsales3@mail.taisaw.com Web: www.taisaw.com

SAW Filter 165.74MHz 27MHz BW (SMD 7.0×5.0 mm)

MODEL NO.: TB1037A

REV. NO.1

A. MAXIMUM RATING:

1. Operating temperature range: -30°C to 65°C
2. Storage temperature range: -40°C to 85°C
3. Input Power Level : 10 dBm
4. Maximum DC Voltage : 10V

RoHS Compliant
Lead free
Lead-free soldering

Electrostatic Sensitive Device

B. Characteristics :

Item	Unit	Min.	Type.	Max.
Center frequency, F_c	MHz	-	165.74	-
Insertion Loss, IL	dB	-	11.1	16.0
1dB Band Width	MHz	27	30.7	
Amplitude Ripple F _c +/-12.5MHz	dB	-	0.6	1.0
Attenuation (Reference level from typical Insertion loss)				
50 ~ 143 MHz	dB	40	48	
187MHz ~ 800 MHz	dB	40	42	
Temperature Coefficient	ppm/°C	-	-94	-
Source Impedance	Ohm	-	50	-
Load Impedance	Ohm	-	50	-

C. Frequency Characteristics :

(1) Wide band Response:(span 300MHz)




Fig1. Horizontal: 30MHz/Div Vertical: 10dB/Div

(2) Pass band Response and Group Time Delay response:






Fig2. Horizontal: 5MHz/Div Vertical: 1dB/Div
Vertical: 100ns/Div

D. Matching Circuit:



$$L1=27\text{nH} \quad C1=36\text{pF} \quad L2=27\text{nH} \quad C2=396\text{pF}$$

E. Outline Drawing:



Pin J –RF input

Pin K –RF input ground

Pin D –RF output

Pin E –RF output ground

Pin A,B,C,F,G,H - Ground


□ : Week Code (Follow the table from planner each year)

Unit : mm

△ : Product / Year Code


Year	2009 2013	2010 2014	2011 2015	2012 2016
Product Code	B	b	<u>B</u>	<u>b</u>

F. PCB Footprint:




G. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE_:

