



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 433.92 MHz SMD 3.0x3.0 mm (BW=1.6 MHz)

TST Part No.: TA1728A

Customer Part No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ David Chang 

Approved by: _____ Bob Chau 

Date: _____ 2015/04/10

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 433.92 MHz

MODEL NO.: TA1728A

REV. NO.:2

A. MAXIMUM RATING:

1. Input Power Level: 20 dB_m
2. DC voltage: 3 V
3. Operating Temperature: -40°C to 85°C
4. Storage Temperature: -40°C to +85° C

RoHS Compliant
Lead free
Lead-free soldering


Electrostatic Sensitive Device (ESD)

B. CHARACTERISTICS:



Item	Unit	Min.	Typical	Max.
Center frequency Fc	MHz	-	433.92	-
Insertion loss 433.12 ~ 434.72 MHz IL	dB	-	2.2	2.9
Amplitude ripple 433.12 ~ 434.72 MHz	dB	-	0.4	1.0
VSWR S11 S22	-	-	1.6	2.0
Attenuation (Reference level from 0 dB)				
10.0 ~ 380.00 MHz	dB	58	61	-
380.00 ~ 423.42 MHz	dB	46	50	-
423.42 ~ 427.00 MHz	dB	4	16	-
443.42 ~ 453.42 MHz	dB	25	30	-
453.42 ~ 460.00 MHz	dB	35	40	-
460.00 ~ 700.00 MHz	dB	50	54	-
700.00 ~ 1000.00 MHz	dB	42	46	-
Source impedance Zs	Ω	-	50	-
Load impedance ZL	Ω	-	50	-



Note. No matching network required for operation at 50Ω

C. MEASUREMENT CIRCUIT:




D. TRANSFER FUNCTION:





E. OUTLINE DRAWING:



B: Input

E: Output

A, C, D, F: Ground

Unit: mm


△ : Year Code (2011->1, 2012->2, ..., 2019->9, 2020->0)

□ : Date Code

Date Code Table:

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z


F.PCB FOOTPRINT:




G. PACKING:

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE:

