



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: ttsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date:

Product Name: SAW Filter 810MHz SMD 3.0×3.0mm

TST Parts No.:TA0478A

Customer Parts No.:_____

Company:_____

Division:_____

Approved by :_____

Date:_____

Checked by:_____Elvis Chiu

Approval by:_____Francis Chen

Date:_____2005/06/06



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 810 MHz

MODEL NO.: TA0478A

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dB_m
2. DC voltage: 5 V
3. Operating Temperature: -40°C to 85°C
4. Storage Temperature: -40°C to +85°C



RoHS Compliant
Lead free
Lead-free soldering

B. CHARACTERISTICS:


Item				Min.	Typ.	Max.
Center frequency	Fc	MHz		-	810	-
Insertion loss	805 ~ 815 MHz	IL	dB	-	2.1	4.3
Amplitude ripple	805 ~ 815 MHz		dB	-	0.5	2.0
Group delay variation	805 ~ 815 MHz		ns	-	14	130
3dB Bandwidth	BW _{-3dB}		MHz	-	27	-
10dB Bandwidth	BW _{-10dB}		MHz	-	31.8	-
20dB Bandwidth	BW _{-20dB}		MHz	-	37.7	-
30dB Bandwidth	BW _{-30dB}		MHz	-	49.6	-
Attenuation (Reference level from 0dB)						
680 ~ 770		MHz	dB	35	53	-
860		MHz	dB	40	49	-
Temperature coefficient of frequency			ppm/K	-	-36	-
Source impedance	Zs		Ω	-	50	-
Load impedance	ZL		Ω	-	50	-

Note1. No matching network required for operation at 50Ω


C. Transfer Function :




Group Delay




D. MEASUREMENT CIRCUIT:



E.OUTLINE DRAWING:




F.PCB FOOTPRINT:



G. PACKING:

1. REEL DIMENSION



2. TAPE DIMENSION

