



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 1585.655 MHz (BW 40.47MHz) SMD 1.1X0.9mm

TST Parts No.:TA2391A

Customer Parts No.:_____

Customer signature required

Company:_____

Division:_____

Approved by :_____

Date:_____

Checked by:_____ Michael Yang *Michael*

Approval by:_____ Andy Yu *Andy Yu*

Date:_____ 2021/08/02

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 1585.655 MHz (BW 40.47Hz) SMD 1.1x0.9x0.5mm

MODEL NO.:TA2391A

REV. NO.:3.0

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: -40°C to +85°C
4. Storage Temperature: -40°C to +105°C
5. Moisture Sensitivity Level: Level 3(MSL3)

RoHS Compliant

Lead-free soldering


Electrostatic Sensitive Device

B. ELECTRICAL CHARACTERISTICS:


Item	Unit	Min.	Type.	Max. -40°C to +85°C
Center Frequency Fc	MHz	-	1585.655	-
Insertion Loss (1565.42~1585.42MHz)	dB	-	1.4	2.2
Insertion Loss (1574.42~1576.42MHz)			1.0	1.4
Insertion Loss (1597.55~1605.89 MHz)			1.6	2.2
VSWR (1565.42~1585.42MHz)		-	1.5	1.8
VSWR (1597.55~1605.89 MHz)		-	1.7	2
Amplitude ripple (1565.42~1605.89MHz)	dB	-	0.6	1.0
Group Delay Variation				
(1565.42~1585.42MHz)	ns		4	5
(1574.42~1576.42MHz)	ns		2	4
(1597.55~1605.89 MHz)	ns		3	5
Attenuation				
10 ~ 960 MHz	dB	40	45	-
1427 ~ 1453 MHz	dB	42	45	-
1453 ~ 1501 MHz	dB	30	35	-
1501 ~ 1525 MHz	dB	20	25	-
1626 ~ 1660 MHz	dB	4	8	-
1710 ~ 1785 MHz	dB	30	35	-
1850 ~ 1910 MHz	dB	40	45	-
1920 ~ 1980 MHz	dB	40	45	-
2110 ~ 2170 MHz	dB	35	40	-
2400 ~ 2500 MHz	dB	35	40	-
2500 ~ 2570 MHz	dB	35	38	-
Temperature coefficient	ppm/°C	-36		
Package size	mm	SMD 1.1x0.9		

C.FREQUENCY CHARACTERISTICS:


S21 response: (span 500MHz)





S21 response: (span 200MHz)




S21 response: (span 4.5GHz)



S11/S22 response:




D. OUTLINE DRAWING:



All tolerances are ± 0.05 mm unless otherwise specified
Coplanarity : 0.1 mm max.

1 to 5 : Pin No.

Unit : mm




Pin No.	Symbol	Function
1	IN	Input
2	GND	Ground
3	GND	Ground
4	OUT	Output
5	GND	Ground


Δ : Year/Month Code (Follow the table)

YEAR/Month	1	2	3	4	5	6	7	8	9	10	11	12
2021	A	B	C	D	E	F	G	H	J	K	L	M
2022	N	P	Q	R	S	T	U	V	W	X	Y	Z
2023	a	b	c	d	e	f	g	h	j	k	l	m
2024	n	p	q	r	s	t	u	v	w	x	y	z
2025	<u>A</u>	<u>B</u>	<u>C</u>	<u>D</u>	<u>E</u>	<u>F</u>	<u>G</u>	<u>H</u>	<u>J</u>	<u>K</u>	<u>L</u>	<u>M</u>
2026	<u>N</u>	<u>P</u>	<u>Q</u>	<u>R</u>	<u>S</u>	<u>T</u>	<u>U</u>	<u>V</u>	<u>W</u>	<u>X</u>	<u>Y</u>	<u>Z</u>
2027	<u>a</u>	<u>b</u>	<u>c</u>	<u>d</u>	<u>e</u>	<u>f</u>	<u>g</u>	<u>h</u>	<u>i</u>	<u>k</u>	<u>l</u>	<u>m</u>
2028	<u>n</u>	<u>p</u>	<u>q</u>	<u>r</u>	<u>s</u>	<u>t</u>	<u>u</u>	<u>v</u>	<u>w</u>	<u>x</u>	<u>y</u>	<u>z</u>

E. MEASUREMENT CIRCUIT:




F. FOOT PRINT :




F. PACKING:

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



G. RECOMMENDED REFLOW PROFILE :

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (20~40sec).
4. Time: 2 times.

