



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Issued Date:

Product Name: SAW IF Filter 70 MHz (package 13.3mm x 6.5 mm)

TST Parts No.: TB0856A

Customer Parts No.: _____


Customer signature required


Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Kazuma Lee 

Approval by: _____ Francis Chen 

Date: _____ 08 / 2 / 2010

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No.3, Industrial 2nd Rd., Ping-Chen Industrial District, Taoyuan, Taiwan, R.O.C.

TEL: 886-3-4690038

FAX: 886-3-4697532

E-mail: tstsales3@mail.taisaw.com Web: www.taisaw.com

SAW Filter 70MHz 24MHz BW (SMD 13.3×6.5 mm)

MODEL NO.: TB0856A

REV. NO.1

A. MAXIMUM RATING:

1. Operating temperature range: -40°C to 85°C
2. Storage temperature range: -40°C to 85°C
3. Input Power Level : 10 dBm
4. Maximum DC Voltage : 10V

RoHS Compliant
Lead free
Lead-free soldering

B. Characteristics :

Item	Unit	Min.	Type.	Max.
Center frequency, F_c	MHz	-	70	-
Insertion Loss, IL	dB	-	18.3	20.0
-1dB bandwidth	MHz	-	23.7	-
-3dB bandwidth	MHz	24.0	24.7	-
-35dB bandwidth	MHz	-	30.0	31.0
Passband Ripple F _c +/- 8MHz	dB	-	0.6	1.0
Group Delay variation F _c +/- 8MHz	nsec	-	23	60
Absolute Delay	unec	-	0.9	-
Temperature Coefficient	ppm/°C	-	-78	-
Source Impedance	Ohm	-	50	-
Load Impedance	Ohm	-	50	-

C. Frequency Characteristics :

(1) Wide band Response:(span 100MHz)




Fig1. Horizontal: 10MHz/Div Vertical: 10dB/Div

(2) Pass band Response and Group Time Delay response:




Fig2. Horizontal: 4MHz/Div Vertical: 1dB/Div






Fig3. Horizontal: 5MHz/Div Vertical: 50ns/Div

D. Matching Circuit:



E. Outline Drawing:



Pin A –RF input

Pin B –RF input ground

Pin G –RF output

Pin H –RF output ground

Pin C, D, E, F, J, K, M, N - Ground


□ : Week Code (Follow the table from planner each year)

Unit : mm

△ : Product / Year Code


Year	2009 2013	2010 2014	2011 2015	2012 2016
Product Code	B	b	<u>B</u>	<u>b</u>

F. PCB Footprint:




G. PACKING:

1. REEL DIMENSION



Unit: mm

2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE_:

