

**UT4407**



Preliminary

Power MOSFET**-13A, -30V P-CHANNEL
POWER MOSFET****DESCRIPTION**

UTC **UT4407** is a P-Channel enhancement mode power field effect transistors are using trench DMOS technology. This advanced technology has been especially tailored to minimize on-state resistance, provide superior switching performance, and withstand high energy pulse in the avalanche and commutation mode. These devices are well suited for high efficiency fast switching applications.

FEATURES

- * $R_{DS(ON)} < 9.5\text{ m}\Omega$ @ $V_{GS} = -10\text{V}$, $I_D = -10\text{A}$
- $R_{DS(ON)} < 15\text{ m}\Omega$ @ $V_{GS} = -4.5\text{V}$, $I_D = -8.0\text{A}$
- * Improved dv/dt capability
- * Fast switching

SYMBOL


SOP-8

ORDERING INFORMATION

Ordering Number		Package	Pin Assignment								Packing
Lead Free	Halogen Free		1	2	3	4	5	6	7	8	
UT4407L-S08-R	UT4407G-S08-R	SOP-8	S	S	S	G	D	D	D	D	Tape Reel

Note: Pin Assignment: S: Source G: Gate D: Drain

		(1) R: Tape Reel (2) S08: SOP-8 (3) G: Halogen Free and Lead Free, L: Lead Free
--	--	---

MARKING

■ **ABSOLUTE MAXIMUM RATINGS** ($T_C = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER			SYMBOL	RATINGS	UNIT
Drain-Source Voltage			V _{DSS}	-30	V
Gate-Source Voltage			V _{GSS}	±20	V
Drain Current	Continuous	T _C = 25°C	I _D	-13	A
		T _C = 100°C		-7.8	A
	Pulsed (Note 2)		I _{DM}	-52	A
Power Dissipation			P _D	4.2	W
Junction Temperature			T _J	+150	°C
Storage Temperature			T _{STG}	-55 ~ +150	°C

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L=0.1\text{mH}$, $I_{AS}=65\text{A}$, $V_{DD}=50\text{V}$, $R_G=25\ \Omega$, Starting $T_J = 25^\circ\text{C}$

■ **THERMAL DATA**

PARAMETER	SYMBOL	RATINGS	UNIT
Junction to Ambient	θ_{JA}	60	$^\circ\text{C/W}$
Junction to Case	θ_{JC}	30	$^\circ\text{C/W}$

Note: The data tested by surface mounted on a 1 inch² FR-4 board with 2OZ copper.


■ **ELECTRICAL CHARACTERISTICS** ($T_J = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	I _D =250μA, V _{GS} =0V	-30			V
BV _{DSS} Temperature Coefficient		ΔBV _{DSS} /ΔT _J	Reference to 25°C , I _D =1mA		-0.03		V/°C
Drain-Source Leakage Current		I _{DSS}	V _{DS} =-30V, V _{GS} =0V			-1	μA
			V _{DS} =-24V, V _{GS} =0V			-10	μA
Gate-Source Leakage Current	Forward	I _{GSS}	V _{GS} =+20V, V _{DS} =0V			+100	nA
	Reverse		V _{GS} =-20V, V _{DS} =0V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	-1.0	-1.6	-2.5	V
V _{GS(TH)} Temperature Coefficient		ΔV _{GS(TH)}			4.0		mV/°C
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =10V, I _D =-10A		8.0	9.5	mΩ
			V _{GS} =4.5V, I _D =-8.0A		12.4	15	mΩ
Forward Transconductance		g _{fs}	V _{DS} =10V, I _D =-10A		13		S
DYNAMIC PARAMETERS							
Input Capacitance		C _{ISS}	V _{GS} =0V, V _{DS} =-15V, f=1.0MHz		3300	4800	pF
Output Capacitance		C _{OSS}			410	700	pF
Reverse Transfer Capacitance		C _{RSS}			280	500	pF
Gate resistance		R _G	V _{GS} =0V, V _{DS} =0V, f=1.0MHz		8.5	12	Ω
SWITCHING PARAMETERS							
Total Gate Charge (Note 1)		Q _G	V _{DS} =-15V, V _{GS} =-4.5V, I _D =-10A		35	56	nC
Gate to Source Charge		Q _{GS}			10.8	16	nC
Gate to Drain Charge		Q _{GD}			10.6	16	nC
Turn-on Delay Time (Note 1)		t _{D(ON)}	V _{DD} =-15V, V _{GS} =-10V, I _D =-1.0A, R _G =6.0Ω		24.5	38	ns
Rise Time		t _R			10.5	16	ns
Turn-off Delay Time		t _{D(OFF)}			156.8	230	ns
Fall-Time		t _F			50	75	ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I _S	V _G =V _D =0V , Force Current			-13	A
Maximum Body-Diode Pulsed Current		I _{SM}				-26	A
Drain-Source Diode Forward Voltage (Note 1)		V _{SD}	I _S =-1.0A, V _{GS} =0V			-1.0	V


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycles $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Test Circuit and Waveforms

Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform



Unclamped Inductive Switching Test Circuit



Unclamped Inductive Switching Waveforms

UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.