

SIGN	DATE	DESCRIPTION	APPROVER
△			
THIS IS CAD DRAWING, DO NOT REVISE MANUALLY!!!			

Material:

- Item ① Terminal body(metal housing): Brass(CuZn),Tin plated
- Item ② Terminal screw: Steel Zinc plating "-" slot type
- Item ③ Wire guard: Stainless steel
- Item ④ Insulator (housing): Thermoplastic (UL94V-0)

Electrical:

- Voltage rating: 300V
- Current rating: 15A
- Wire range:
- Solid wire(AWG): 14-24
- Stranded wire(AWG): 14-24
- Toque(Lb-In): 3.2
- Screw: M2.6
- Wire strip length: 5-6mm
- Withstanding Voltage: 1.6KV
- Operating temperature: -40°C to +115°C
- Soldering temperature: 250°C ±10°C/5 Sec
- Safety Approval: cULus



T9 xx 21 x 0 xxxx G

	Color		
02 2 CONTACTS	0 Black (RAL9005)	0000: "@" Logo	RoHS
03 3 CONTACTS	5 Green(RAL6018/T)	000A: "ANYTEK" Logo	Pb<40,000ppm
... ..	6 Blue (RAL5015/A)	Any special item by	
24 24 CONTACTS	8 Grey(RAL7035/D)	customer request.	
	C Green(RAL 6018/U)	please contact sales	
		department.	

N = Number of poles
 Dim L=Nx5.08
 Dim P=(N-1)x5.08

	Dim L	Dim P
2-6p	±0.15	±0.15
7-12p	±0.30	±0.30
13-18p	±0.35	±0.35
19-24p	±0.40	±0.40

ANYTEK

CUSTOMER COPY

ALL RIGHTS RESERVED. REPRODUCTION OR ISSUE TO THIRD PARTIES IN ANY FORM WHATSOEVER IS NOT PERMITTED WITHOUT WRITTEN AUTHORITY FROM THE PROPRIETOR. PROPERTY OF ANYTEK TECHNOLOGY CO., LTD

TITLE	T9 - 5.08mm Series "-"						
PART NO.	T9xx21x0xxxxG				DWG NO.	8T90002	
APPROVED	CHECKED	DESIGNED	DRAWN	CUST NO.	Tolerance		
		Tason 2010.11.29	Tason 2010.11.29		UNIT: mm		X. ±0.50
					SCALE: NONE		X.X ±0.30
					SHEET: 01/01		REV: B
						X* ±1°	