



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Name: IF SAW Filter 559.5 MHz SMD 3.8x3.8 mm (BW=0.6 MHz)

TST Parts No.: TB1386AA3610

Customer Parts No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Hayley Chou *Hayley Chou*

Approval by: _____ Andy Yu *Andy Yu*

Date: _____ 2020/11/16

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 559.5 MHz

MODEL NO.: TB1386AA3610

REV. NO.:1.0

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage: 3 V
3. Operating Temperature: -40 °C to +105 °C
4. Storage Temperature: -40 °C to +105 °C
5. Moisture Sensitivity Level: Level 1 (MSL 1)

RoHS Compliant

Lead-free soldering


Electrostatic Sensitive Device (ESD)

B. ELECTRICAL CHARACTERISTICS:

Temperature range for specification: 25 °C



Item	Unit	Min.	Typ.	Max.
Center Frequency F_c	MHz	-	559.5	-
Minimum Insertion Loss IL_{min}	dB	-	3.1	4.0
1 dB Bandwidth	MHz	0.6	1.3	-
9 dB Bandwidth	MHz	-	5	6.8
11.5 dB Bandwidth	MHz	-	6.2	9
12 dB Bandwidth	MHz	-	6.3	24
Amplitude Ripple (559.2~559.8 MHz)	dB	-	0.3	1.5
Absolute Group Delay	μsec	-	0.2	1
Group Delay Ripple (559.2~559.8 MHz)	nsec	-	25	250
Attenuation (Reference level from 0 dB)				
460 ~ 505.5 MHz	dB	35	46	-
613.5 ~ 660 MHz	dB	35	49	-
Temperature Coefficient of Frequency	ppm/°C	-36		



C. MEASUREMENT CIRCUIT:



L1=3.6nH, L2=2.8nH, C1=4pF, C2=4.7pF


D. FREQUENCY CHARACTERISTICS:






Reflection Functions:


S11



S22



E. OUTLINE DRAWING:



Unit : mm

Not Specified Tolerance : ± 0.15 mm

Pin No.	Symbol	Function
1	GND	Ground
2	IN	Input
3	GND	Ground
4	GND	Ground
5	GND	Ground
6	OUT	Output
7	GND	Ground
8	GND	Ground

△: Product / Year Code

□: Date Code (Follow the table from planner each year)


△ Product / Year Code

Year	2019 2021 2023 2025	2020 2022 2024 2026
Product Code	B	b

Date Code Table:

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z


F. PCB FOOTPRINT:




G. PACKING: (Ref. WI-75M03)

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE:

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C+0/-5°C peak (20~40sec).
4. Time: 2 times.

