

The information provided herein is from CONNPLY Electronic Co., Ltd. and is confidential. Any disclosure to a party other than the recipient is prohibited. The intellectual properties and its rights contained herein, including but not limited to, trademarks, patents, copyrights, trade secrets, and technical know-how, are owned exclusively by CONNPLY or its affiliates. Unauthorized use or modification is strictly prohibited without prior written consent from CONNPLY. All intellectual properties provided herein are for reference purposes only and does not constitute authorization of its use in any format or manner. CONNPLY may enforce its intellectual property rights at its own discretion, failures or delays to exercise such rights does not constitute a waiver of such rights.

1. SPECIFICATIONS

- Contact Rating: 50mA at 12Vdc
- Insulation Resistance: 100MΩ min.
- Contact Resistance: 50mΩ max.
- Dielectric Withstanding Voltage: 250V AC(rms) for 1 minute.
- Operating Life: 100,000 cycles
- Travel: 0.25±0.1mm
- Operation Temperature Range: -25°C to +70°C

2. PRODUCT NUMBER CODE:

DS1041-11 - X X X X X X X X

- Operating Life
10: 100,000 cycles
20: 200,000 cycles
- Sheath Support
X: W/O Sheath
- Operating force
260: 260gf
- Packing type
A: polybag
- Actuator color
K: Black
- Housing color
K: Black
- Profile Height(Dim H)
060: 6.0mm 065: 6.5mm
070: 7.0mm 075: 7.5mm
- No. of contacts
4: 4 pos

GENERAL TOLERANCE

X.	±0.60
.X	±0.38
.XX	±0.25

ANGLE TOLERANCE

X.	±5°
.X	±3°
.XX	±2°

PROJECTION

UNIT	mm
SHEET SIZE	A4

TITLE

SERIES	DS1041-11 SERIES
--------	------------------

DRAWING TYPE

CUSTOMER	1:1
----------	-----

SCALE

SHEET	1 OF 2
-------	--------

DRAWING NO.

C-DS1041-11-XXXXXXX-A

晨翔电子有限公司
CONNPLY CONNPLY ELECTRONIC CO. LTD

