



**20N50K-MT****Power MOSFET****20A, 500V N-CHANNEL
POWER MOSFET****DESCRIPTION**

The UTC **20N50K-MT** is a N-channel power MOSFET using UTC's advanced technology to provide the customers with minimum on-state resistance, superior switching performance and withstand high energy pulse in the avalanche and commutation mode.

FEATURES

* $R_{DS(ON)} \leq 0.28 \Omega$ @ $V_{GS}=10V$, $I_D=10A$


* High Switching Speed

SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
20N50KL-TA3-T	20N50KG-TA3-T	TO-220	G	D	S	Tube
20N50KL-TF1-T	20N50KG-TF1-T	TO-220F1	G	D	S	Tube
20N50KL-TF2-T	20N50KG-TF2-T	TO-220F2	G	D	S	Tube
20N50KL-TF3-T	20N50KG-TF3-T	TO-220F	G	D	S	Tube
20N50KL-T3B-T	20N50KG-T3B-T	TO-3PB	G	D	S	Tube
20N50KL-T3P-T	20N50KG-T3P-T	TO-3P	G	D	S	Tube
20N50KL-T3N-T	20N50KG-T3N-T	TO-3PN	G	D	S	Tube

Note: Pin Assignment: G: Gate D: Drain S: Source

	(1) Packing Type	(1) T: Tube
	(2) Package Type	(2) TA3: TO-220, TF1: TO-220F1, TF2: TO-220F2, TF3: TO-220F, T3B: TO-3PB, T3P: TO-3P, T3N: TO-3PN
	(3) Green Package	(3) G: Halogen Free and Lead Free, L: Lead Free

MARKING

■ **ABSOLUTE MAXIMUM RATINGS** ($T_C=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	500	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current	Continuous	I_D	20	A
	Pulsed (Note 2)	I_{DM}	80	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	1000	mJ
Peak Diode Recovery dv/dt		dv/dt	2.2	V/ns
Power Dissipation	TO-220	P_D	200	W
	TO-220F/TO-220F1		43	W
	TO-220F2			
	TO-3PB/TO-3P TO-3PN		220	W
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L = 10\text{mH}$, $I_{AS} = 14\text{A}$, $V_{DD} = 50\text{V}$, $R_G = 25\Omega$, Starting $T_J = 25^{\circ}\text{C}$

4. $I_{SD} \leq 20\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J = 25^{\circ}\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATING	UNIT
Junction to Ambient	TO-220/TO-220F	θ_{JA}	62.5	$^{\circ}\text{C}/\text{W}$
	TO-220F1/TO-220F2			
	TO-3PB/TO-3P TO-3PN		40	$^{\circ}\text{C}/\text{W}$
Junction to Case	TO-220	θ_{JC}	0.625	$^{\circ}\text{C}/\text{W}$
	TO-220F/TO-220F1		2.9	$^{\circ}\text{C}/\text{W}$
	TO-220F2			
	TO-3PB/TO-3P TO-3PN		0.56	$^{\circ}\text{C}/\text{W}$


■ **ELECTRICAL CHARACTERISTICS** ($T_C=25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	I _D =250μA, V _{GS} =0V	500			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} =500V, V _{GS} =0V				μA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =+30V, V _{DS} =0V			+100	nA
	Reverse		V _{GS} =-30V, V _{DS} =0V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2.0		4.0	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =10V, I _D =10A			0.28	Ω
DYNAMIC PARAMETERS							
Input Capacitance		C _{ISS}	V _{GS} =0V, V _{DS} =25V, f=1.0MHz		2450		pF
Output Capacitance		C _{OSS}			275		pF
Reverse Transfer Capacitance		C _{RSS}			16.5		pF
SWITCHING PARAMETERS							
Total Gate Charge (Note 1)		Q _G	V _{DS} =100V, V _{GS} =10V, I _D =20A I _G = 1mA (Note1, 2)		53		nC
Gate to Source Charge		Q _{GS}			11		nC
Gate to Drain Charge		Q _{GD}			13		nC
Turn-ON Delay Time (Note 1)		t _{D(ON)}	V _{DS} =100V, V _{GS} =10V, I _D =20A, R _G =25Ω (Note1, 2)		32		ns
Rise Time		t _R			30		ns
Turn-OFF Delay Time		t _{D(OFF)}			162		ns
Fall-Time		t _F			70		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I _S				20	A
Maximum Body-Diode Pulsed Current		I _{SM}				80	A
Drain-Source Diode Forward Voltage (Note 1)		V _{SD}	I _S =20A, V _{GS} =0V			1.4	V
Body Diode Reverse Recovery Time (Note 1)		t _{rr}	I _S =20A, V _{GS} =0V, V _R =400V		412		ns
Reverse Recovery Charge		Q _{rr}	dl _F /dt=100A/μs (Note 1)		6.5		μC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.