



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 1438 MHz (BW 50MHz) SMD 3X3 mm

TST Part No.: TA2726AA3112

Customer Part No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Michael Yang *Michael*

Approval by: _____ Andy Yu *Andy Yu*

Date: _____ 2020/12/06

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 1438MHz

MODEL NO.:TA2726AA3112

REV. NO.:1.0

A. MAXIMUM RATING:

1. Input Power Level: 15 dBm
2. DC Voltage : 3V
3. Operating Temperature: -40℃ to +85℃
4. Storage Temperature: -40℃ to +85℃
5. Moisture Sensitive Level (MSL): Level 1

RoHS Compliant

Lead-free soldering

Electrostatic Sensitive Device (ESD)

B. ELECTRICAL CHARACTERISTICS:

Terminating source impedance (single) : $Z_s = 50 \Omega$

Terminating load impedance (single) : $Z_L = 50 \Omega$


Item	Unit	Min	Type.	Max
Center Frequency F_c	MHz	-	1438.	-
Insertion Loss (1413~1463 MHz) IL	dB		4.2	5.0
VSWR (1413~1463 MHz)			1.6	2.4
G_Delay Ripple	nS		10	15
Amplitude ripple				
(1413~1463 MHz)	dB		1.7	3.0
Attenuation				
10 ~ 1360 MHz	dB	40	46	
1360 ~ 1385 MHz	dB	20	42	
1490 ~ 1565 MHz	dB	18	26	
1565 ~ 2900 MHz	dB	40	43	
Temperature coefficient	ppm/°C	-36		
Package size	mm	SMD 3x3		

C... TEST CIRCUIT:


(2): Unbalance Port

(5): Unbalance Port


Others: Ground




D. Frequency Characteristics: S21 response :(Span 500MHz)




S21 response :(Span 100MHz)




S21 response :(Span 4.5GHz)



S11/S22 response :(Span 500MHz)




E.OUTLINE DRAWING:



Unit : mm

Not Specified Tolerance : ± 0.15 n



Pin No.	Symbol	Function
1	GND	Ground
2	IN	Input
3	GND	Ground
4	GND	Ground
5	OUT	Output
6	GND	Ground

Data code : See the table

WK	01	02	...	26	27	28	...	52
Code	A	B	...	Z	a	b	...	z


△ Year code : See the table

Year	2008	2009	2010	2011	...	2019	2020
Code	8	9	0	1	...	9	0


F. PACKING:

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION.



G. RECOMMENDED REFLOW PROFILE :

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 260°C +0/-5°C peak (20~40sec).
4. Time: 2 times.

