



**2N60Z****Power MOSFET****2.0A, 600V N-CHANNEL
POWER MOSFET****DESCRIPTION**

The UTC **2N60Z** is a high voltage power MOSFET and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and have a high rugged avalanche characteristics. This power MOSFET is usually used at high speed switching applications in power supplies, PWM motor controls, high efficient AC to DC converters and bridge circuits.

FEATURES

- * $R_{DS(ON)} \leq 5.0 \Omega$ @ $V_{GS} = 10V$, $I_D = 1.0A$
- * Fast switching capability
- * Avalanche energy specified
- * Improved dv/dt capability, high ruggedness


SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
2N60ZL-TF3-T	2N60ZG-TF3-T	TO-220F	G	D	S	Tube
2N60ZL-TM3-T	2N60ZG-TM3-T	TO-251	G	D	S	Tube
2N60ZL-TN3-T	2N60ZG-TN3-T	TO-252	G	D	S	Tube
2N60ZL-TN3-R	2N60ZG-TN3-R	TO-252	G	D	S	Tape Reel
2N60ZL-T60-K	2N60ZG-T60-K	TO-126	G	D	S	Bulk

Note: Pin Assignment: G: Gate D: Drain S: Source

2N60ZG-TF3-T (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube, R: Tape Reel, B: Bulk (2) TF3: TO-220F, TM3: TO-251, TN3: TO-252 T60: TO-126 (3) G: Halogen Free and Lead Free, L: Lead Free
--	---

■ MARKING



■ **ABSOLUTE MAXIMUM RATINGS** ($T_C = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	600	V
Gate-Source Voltage		V_{GSS}	± 20	V
Drain Current	Continuous	I_D	2	A
	Pulsed (Note 2)	I_{DM}	8	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	86.5	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	3.7	V/ns
Power Dissipation	TO-220F	P_D	23	W
	TO-251/TO-252		40	W
	TO-126		20	W
Junction Temperature		T_J	+150	$^\circ\text{C}$
Operating Temperature		T_{OPR}	-55 ~ +150	$^\circ\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^\circ\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L=30\text{mH}$, $I_{AS}=2.4\text{A}$, $V_{DD}=50\text{V}$, $R_G=25\ \Omega$, Starting $T_J = 25^\circ\text{C}$

4. $I_{SD}\leq 2.0\text{A}$, $di/dt\leq 200\text{A}/\mu\text{s}$, $V_{DD}\leq BV_{DSS}$, Starting $T_J = 25^\circ\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220F	θ_{JA}	62.5	$^\circ\text{C/W}$
	TO-251/TO-252		110	$^\circ\text{C/W}$
	TO-126		130	$^\circ\text{C/W}$
Junction to Case	TO-220F	θ_{JC}	5.5	$^\circ\text{C/W}$
	TO-251/TO-252		3.125 (Note)	$^\circ\text{C/W}$
	TO-126		6.25 (Note)	$^\circ\text{C/W}$

Note: Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.


■ **ELECTRICAL CHARACTERISTICS** ($T_J = 25^\circ\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	V _{GS} = 0V, I _D = 250μA	600			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} = 600V, V _{GS} = 0V			10	μA
Gate-Source Leakage Current	Forward	I _{GSS}	V _{GS} = 20V, V _{DS} = 0V			10	μA
	Reverse		V _{GS} = -20V, V _{DS} = 0V			-10	μA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} = V _{GS} , I _D = 250μA	2.0		4.0	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} = 10V, I _D =1.0A			5.0	Ω
DYNAMIC CHARACTERISTICS							
Input Capacitance		C _{ISS}	V _{DS} =25V, V _{GS} =0V, f =1MHz		432.1		pF
Output Capacitance		C _{OSS}			39.8		pF
Reverse Transfer Capacitance		C _{RSS}			7.9		pF
SWITCHING CHARACTERISTICS							
Total Gate Charge		Q _G	V _{DS} =480V, V _{GS} =10V, I _D =2.0A, I _G =1mA (Note 1, 2)		19		nC
Gate-Source Charge		Q _{GS}			5.4		nC
Gate-Drain Charge		Q _{GD}			4.3		nC
Turn-On Delay Time		t _{D (ON)}	V _{DD} =100V, V _{GS} =10V, I _D =2.0A, R _G =25Ω (Note 1, 2)		5.4		ns
Turn-On Rise Time		t _R			16.6		ns
Turn-Off Delay Time		t _{D (OFF)}			55		ns
Turn-Off Fall Time		t _F			30.5		ns
DRAIN-SOURCE DIODE CHARACTERISTICS							
Maximum Continuous Drain-Source Diode Forward Current		I _S				2	A
Maximum Pulsed Drain-Source Diode Forward Current		I _{SM}				8	A
Drain-Source Diode Forward Voltage		V _{SD}	V _{GS} = 0 V, I _{SD} = 2.0 A			1.4	V
Reverse Recovery Time		t _{rr}	V _{GS} = 0 V, I _{SD} = 2.0A,		222.6		ns
Reverse Recovery Charge		Q _{rr}	di/dt = 100 A/μs (Note 1)		3.1		μC


Notes: 1. Pulse Test : Pulse width $\leq 300\mu s$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating ambient temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


TYPICAL CHARACTERISTICS



■ TYPICAL CHARACTERISTICS (Cont.)



■ TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.