



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specifications Approval Sheet

Product Description: SAW Filter 2450 MHz SMD 3.0X3.0 mm (BW=50MHz)

TST Part No.: TA1198A

Customer Part No.: _____

Customer signature required

Company: _____

Division: _____

Approved by : _____

Date: _____

Checked by: _____ Bob Chau

Approved by: _____ Francis Chen

Date: _____ 4, 21, 2010

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com

Web: www.taisaw.com

SAW Filter 2450 MHz

MODEL NO.:TA1198A

REV. NO.:1

A. MAXIMUM RATING:


1. Input Power Level: 10 dBm
2. DC Voltage : 3V
3. Operating Temperature: -20°C to +70°C
4. Storage Temperature: -30°C to +85°C

RoHS Compliant
Lead free
Lead-free soldering

B. ELECTRICAL CHARACTERISTICS:

Item	Unit	Min.	Typ.	Max.	Note
Center Frequency Fc	MHz	-	2450	-	-
Insertion Loss (2425~2475 MHz) IL	dB	-	2.5	3.5	-
Amplitude Ripple (2425~2475 MHz)	dB	-	0.9	2	-
VSWR (2425~2475 MHz)		-	2	2.5	-
Attenuation (Reference level from 0 dB)					
D.C ~ 2330 MHz	dB	25	31	-	-
2330 ~ 2360 MHz	dB	30	40	-	-
2600 ~ 3500 MHz	dB	30	38	-	-
Temperature Coefficient of Frequency	ppm/°C	-	-36	-	-

C.OUTLINE DRAWING:




△ : Year Code (2009->9, 2010->0,..., 2018->8)


□ : Date Code (W01->A,W02->B,...W27->a,...,W52->z)

D. MEASUREMENT CIRCUIT:




HP Network analyzer



E. PCB Footprint:




F. Frequency Characteristics :




Reflection Functions :

S11




S22




G. PACKING:

1. REEL DIMENSION

(Reel Count : 7"=1000 ; 13"=3000)



2.TAPE DIMENSION



H. RECOMMENDED REFLOW PROFILE :

