



RAYSTAR

RAYSTAR Optronics, Inc.
曜凌光電股份有限公司



曜凌光電股份有限公司
Raystar Optronics, Inc.

T: +886-4-2565-0761 | F: +886-4-2565-0760

salescontact@raystar-optronics.com | www.raystar-optronics.com

RFC570W-SLW-DNN

General Specifications

- Size: 5.7 inch
- Dot Matrix: 320 x RGB x 240(TFT) dots
- Module dimension: 143.5 x 104.1 x 12.35 mm
- Active area: 115.2 x 86.4 mm
- Dot pitch: 0.12 x 0.36 mm
- LCD type: TFT, Normally White, Transmissive
- Drive IC: HX8218+HX8615
- Interface: 18-bit RGB
- View Direction: 6 o'clock
- Gray Scale Inversion Direction: 12 o'clock
- Aspect Ratio: 4:3
- Backlight Type: LED, Normally White
- Touch Panel: Without Touch Panel
- Surface: Glare

Interface

LCM PIN Definition


Pin	Symbol	Function
1	GND	Ground
2	CK	Clock signal for sampling each data signal(DCLK)
3	Hsync	Horizontal synchronous signal
4	Vsync	Vertical synchronous signal
5	GND	Ground
6	R0	Red Data bit(LSB)
7	R1	Red Data bit
8	R2	Red Data bit
9	R3	Red Data bit
10	R4	Red Data bit
11	R5	Red Data bit(MSB)
12	GND	Ground
13	G0	Green Data bit(LSB)
14	G1	Green Data bit
15	G2	Green Data bit
16	G3	Green Data bit
17	G4	Green Data bit
18	G5	Green Data bit(MSB)
19	GND	Ground
20	B0	Blue Data bit(LSB)
21	B1	Blue Data bit
22	B2	Blue Data bit
23	B3	Blue Data bit
24	B4	Blue Data bit
25	B5	Blue Data bit(MSB)
26	GND	Ground
27	NC	No connect
28	VCC	+3.3V power supply
29	VCC	+3.3V power supply
30	R/L	Selection signal for horizontal scanning direction (L: Normally H: Right-and-left reversal)

31	U/D	Selection signal for vertical scanning direction (H: Normally L: Up-and-Down reversal)
32	NC	No connect
33	GND	Ground

Backlight PIN Definition

Pin No.	Symbol	Description
1	K	Black, LED_ Cathode
2	NC	No connection
3	A	Red, LED_ Anode

Contour Drawing



Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

1. Operating conditions:

Item	Symbol	Condition	Min	Typ	Max	Unit
Supply Voltage For LCM	VCC	—	3.0	3.3	3.6	V
Supply Current For LCM	ICC	—	—	110	170	mA
Power Consumption	—	—	—	363	612	mW