

# BSS138-AU


## 50V N-Channel Enhancement Mode MOSFET - ESD Protected

### FEATURES

- $R_{DS(ON)}$ ,  $V_{GS}@10V, I_{DS}@500mA=3\Omega$
- $R_{DS(ON)}$ ,  $V_{GS}@4.5V, I_{DS}@200mA=4\Omega$
- $R_{DS(ON)}$ ,  $V_{GS}@2.5V, I_{DS}@100mA=6\Omega$
- Advanced Trench Process Technology
- High Density Cell Design For Ultra Low On-Resistance
- Very Low Leakage Current In Off Condition
- Specially Designed for Battery Operated Systems, Solid-State Relays Drivers : Relays, Displays, Lamps, Solenoids, Memories, etc.
- ESD Protected
- Lead free in compliance with EU RoHS2.0 (2011/65/EU & 2015/865/EU directive)
- Green molding compound as per IEC61249 Std. . (Halogen Free)
- Acquire quality system certificate : TS16949
- AEC-Q101 qualified


### MECHANICAL DATA

- Case: SOT-23 Package
- Terminals: Solderable per MIL-STD-750, Method 2026
- Apporx. Weight: 0.0003 ounce, 0.0084 gram
- Marking: 138



### SOT-23

Unit : inch(mm)



### Maximum Ratings and Thermal Characteristics ( $T_A=25^\circ\text{C}$ unless otherwise noted )

| PARAMETER                                                                     | Symbol          | Limit        | Units              |
|-------------------------------------------------------------------------------|-----------------|--------------|--------------------|
| Drain-Source Voltage                                                          | $V_{DS}$        | 50           | V                  |
| Gate-Source Voltage                                                           | $V_{GS}$        | $\pm 20$     | V                  |
| Continuous Drain Current                                                      | $I_D$           | 300          | mA                 |
| Pulsed Drain Current <sup>1)</sup>                                            | $I_{DM}$        | 2000         | mA                 |
| Maximum Power Dissipation<br>$T_A=25^\circ\text{C}$<br>$T_A=75^\circ\text{C}$ | $P_D$           | 350<br>210   | mW                 |
| Operating Junction and Storage Temperature Range                              | $T_J, T_{STG}$  | -55 to + 150 | $^\circ\text{C}$   |
| Junction-to Ambient Thermal Resistance(PCB mounted) <sup>2</sup>              | $R_{\theta JA}$ | 357          | $^\circ\text{C/W}$ |

Note: 1. Maximum DC current limited by the package


2. Surface mounted on FR4 board,  $t < 5$  sec

# BSS138-AU


## ELECTRICAL CHARACTERISTICS

| Parameter                        | Symbol       | Test Condition                                                                 | Min. | Typ. | Max.     | Units    |
|----------------------------------|--------------|--------------------------------------------------------------------------------|------|------|----------|----------|
| Static                           |              |                                                                                |      |      |          |          |
| Drain-Source Breakdown Voltage   | $BV_{DSS}$   | $V_{GS}=0V$ , $I_D=10\mu A$                                                    | 50   | -    | -        | V        |
| Gate Threshold Voltage           | $V_{GS(th)}$ | $V_{DS}=V_{GS}$ , $I_D=250\mu A$                                               | 0.8  | -    | 1.5      | V        |
| Drain-Source On-State Resistance | $R_{DS(on)}$ | $V_{GS}=2.5V$ , $I_D=100mA$                                                    | -    | 2.8  | 6.0      | $\Omega$ |
| Drain-Source On-State Resistance | $R_{DS(on)}$ | $V_{GS}=4.5V$ , $I_D=200mA$                                                    | -    | 1.8  | 4.0      |          |
| Drain-Source On-State Resistance | $R_{DS(on)}$ | $V_{GS}=10V$ , $I_D=500mA$                                                     | -    | 1.6  | 3.0      |          |
| Zero Gate Voltage Drain Current  | $I_{DSS}$    | $V_{DS}=50V$ , $V_{GS}=0V$                                                     | -    | -    | 1        | $\mu A$  |
| Gate Body Leakage                | $I_{GSS}$    | $V_{GS}=\pm 20V$ , $V_{DS}=0V$                                                 | -    | -    | $\pm 10$ | $\mu A$  |
| Forward Transconductance         | $g_{fs}$     | $V_{DS}=10V$ , $I_D=250mA$                                                     | 100  | -    | -        | mS       |
| Dynamic                          |              |                                                                                |      |      |          |          |
| Total Gate Charge                | $Q_g$        | $V_{DS}=25V$ , $I_D=250mA$<br>$V_{GS}=4.5V$                                    | -    | -    | 1.0      | nC       |
| Turn-On Time                     | $t_{on}$     | $V_{DD}=30V$ , $R_L=100\Omega$<br>$I_D=300mA$ , $V_{GEN}=10V$<br>$R_G=6\Omega$ | -    | -    | 40       | ns       |
| Turn-Off Time                    | $t_{off}$    |                                                                                | -    | -    | 150      |          |
| Input Capacitance                | $C_{iss}$    | $V_{DS}=25V$ , $V_{GS}=0V$<br>$f=1.0MHz$                                       | -    | -    | 50       | pF       |
| Output Capacitance               | $C_{oss}$    |                                                                                | -    | -    | 10       |          |
| Reverse Transfer Capacitance     | $C_{rss}$    |                                                                                | -    | -    | 5        |          |
| Source-Drain Diode               |              |                                                                                |      |      |          |          |
| Diode Forward Voltage            | $V_{SD}$     | $I_S=250mA$ , $V_{GS}=0V$                                                      | -    | 0.82 | 1.2      | V        |
| Continuous Diode Forward Current | $I_S$        | -                                                                              | -    | -    | 300      | mA       |
| Pulse Diode Forward Current      | $I_{SM}$     | -                                                                              | -    | -    | 2000     | mA       |

**Switching Test Circuit**








**Gate Charge Test Circuit**




# BSS138-AU


Typical Characteristics Curves ( $T_A=25^\circ\text{C}$ , unless otherwise noted)




## BSS138-AU




**Fig.6 - Gate Charge Waveform**



**Fig.7 Source-Drain Diode Forward Voltage**



**Fig.8 - Threshold Voltage vs Temperature**




**Fig.9 - Breakdown Voltage vs Junction Temperature**

# BSS138-AU

## MOUNTING PAD LAYOUT

SOT-23

Unit : inch(mm)



## ORDER INFORMATION

- Packing information
  - T/R - 12K per 13" plastic Reel
  - T/R - 3K per 7" plastic Reel

# BSS138-AU


## Part No\_packing code\_Version

BSS138-AU\_R1\_000A1

BSS138-AU\_R2\_000A1

For example :

RB500V-40\_R2\_00001



| Packing Code XX                      |                      |                                  |                      | Version Code XXXXX |                      |                                       |
|--------------------------------------|----------------------|----------------------------------|----------------------|--------------------|----------------------|---------------------------------------|
| Packing type                         | 1 <sup>st</sup> Code | Packing size code                | 2 <sup>nd</sup> Code | HF or RoHS         | 1 <sup>st</sup> Code | 2 <sup>nd</sup> ~5 <sup>th</sup> Code |
| Tape and Ammunition Box (T/B)        | A                    | N/A                              | 0                    | HF                 | 0                    | serial number                         |
| Tape and Reel (T/R)                  | R                    | 7"                               | 1                    | RoHS               | 1                    | serial number                         |
| Bulk Packing (B/P)                   | B                    | 13"                              | 2                    |                    |                      |                                       |
| Tube Packing (T/P)                   | T                    | 26mm                             | X                    |                    |                      |                                       |
| Tape and Reel (Right Oriented) (TRR) | S                    | 52mm                             | Y                    |                    |                      |                                       |
| Tape and Reel (Left Oriented) (TRL)  | L                    | PANASERT T/B CATHODE UP (PBCU)   | U                    |                    |                      |                                       |
| FORMING                              | F                    | PANASERT T/B CATHODE DOWN (PBCD) | D                    |                    |                      |                                       |



## BSS138-AU

---

### Disclaimer

- Reproducing and modifying information of the document is prohibited without permission from Panjit International Inc..
- Panjit International Inc. reserves the rights to make changes of the content herein the document anytime without notification. Please refer to our website for the latest document.
- Panjit International Inc. disclaims any and all liability arising out of the application or use of any product including damages incidentally and consequentially occurred.
- Panjit International Inc. does not assume any and all implied warranties, including warranties of fitness for particular purpose, non-infringement and merchantability.
- Applications shown on the herein document are examples of standard use and operation. Customers are responsible in comprehending the suitable use in particular applications. Panjit International Inc. makes no representation or warranty that such applications will be suitable for the specified use without further testing or modification.
- The products shown herein are not designed and authorized for equipments relating to human life and for any applications concerning life-saving or life-sustaining, such as medical instruments, aerospace machinery et cetera. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify Panjit International Inc. for any damages resulting from such improper use or sale.
- Since Panjit uses lot number as the tracking base, please provide the lot number for tracking when complaining.