



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Product Specification Approval Sheet

Product Name: SAW Filter 243 MHz SMD 7.0x5.0 mm(BW=0.05 MHz)

TST Parts No.:TB0208C

Customer Parts No.:_____

Customer signature required

Company:_____

Division:_____

Approved by : _____

Date:_____

Checked by:_____ Anne Chen 

Approved by:_____ Bob Chau 

Date:_____ 2016/12/28

1. Customer signed back is required before TST can proceed with sample build and receive orders.
2. Orders received without customer signed back will be regarded as agreement on the specifications.
3. Any specifications changes must be approved upon by both parties and a new revision of specifications shall be released to reflect the changes.



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SAW Filter 243MHz

MODEL NO.:TB0208C

REV. NO.:1

A. MAXIMUM RATING:

1. Input Power Level: 10 dBm
2. DC Voltage : 15V
3. Operating Temperature: -25°C to 60°C
4. Storage Temperature: -30°C to 70°C


RoHS Compliant
Lead free
Lead-free soldering

Electrostatic Sensitive Device (ESD)


B. ELECTRICAL CHARACTERISTICS:

Item	Unit	Min.	Type.	Max.	Note
Center frequency, Fc	MHz	242.988	243	243.012	1
Minimum Insertion Loss, (Fc ±25KHz) IL	dB	-	3.7	6.0	1
Passband Ripple (Fc ±25KHz)	dB	-	0.2	1.0	1
Group delay ripple (Fc ±25KHz), GD	μs	-	0.5	2.0	1
Attenuation:(Reference level from Min IL)					
Fc - 115 to Fc - 1 MHz	dB	50	63	-	-
Fc - 1 to Fc - 0.6 MHz	dB	42	64	-	-
Fc - 0.6 to Fc - 0.4 MHz	dB	29	68	-	-
Fc + 0.4 to Fc + 0.6 MHz	dB	29	64	-	-
Fc + 0.6 to Fc + 1 MHz	dB	42	63	-	-
Fc + 1 to Fc + 115 MHz	dB	50	55	-	-

Note1. The standard definitions is in JIS C 6703



C.OUTLINE DRAWING:



Pin configuration

#9 Input #4 Output
 #10 Balance input or input ground
 #5 Balance output or output ground
 #1,2,3,6,7,8 To be grounded
 Unit mm

Marking name : **208**

△: year code

Product Year
Code

Year	2017 2021	2018 2022	2019 2023	2020 2024
Product Code	B	b	<u>B</u>	<u>b</u>


□ : Week code

Week Code Table



WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z



D. MEASUREMENT CIRCUIT:

50 Ohm Test circuit (single-ended / single-ended)



E. Frequency Characteristics :







F. PACKING:

1. REEL DIMENSION

(Please refer to FR-75D10 for packing quantity)



2. TAPE DIMENSION



Direction of Feed

G. RECOMMENDED REFLOW PROFILE :

1. Preheating shall be fixed at 150~180°C for 60~90 seconds.
2. Ascending time to preheating temperature 150°C shall be 30 seconds min.
3. Heating shall be fixed at 220°C for 50~80 seconds and at 245~260°C peak (min. 10sec).
4. Time : 2 times.

