

TFT DISPLAY SPECIFICATION



RAYSTAR

RAYSTAR Optronics, Inc.
曜凌光電股份有限公司



曜凌光電股份有限公司 Raystar Optronics, Inc.

T: +886-4-2565-0761 | F: +886-4-2565-0760

salescontact@raystar-optronics.com | www.raystar-optronics.com

RFK1010L-AYH-LNG

General Specifications

- Screen Diagonal: 10.1 inch
- Number of Pixels: 1280 x 3(R GB) x 800 dots
- Module dimension: 257.96 x 168.6 x 9.48 mm
- Active area: 216.96 (H) x 135.6(V) mm
- Pixel pitch: 0.1695 × 0.1695 mm
- Display Mode: Normally Black , Transmissive
- Viewing Angle: 80/80/80/80 (IPS)
- Pixel Arrangement: R.G.B. Vertical Stripe
- Drive IC: EK79202B1
- Backlight Type: LED, Normally White
- Aspect Ratio: 16:10
- Interface: LVDS
- PCAP FW Version: 80
- PCAP IC: GT928
- PCAP Interface: I2C
- PCAP Resolution: 1280*800
- Touch Panel: Projected Capacitive Touch Panel, PCAP
- Surface: Glare

Interface

Interface Connector


Pin No.	Symbol	I/O	Function
1	NC	-	No connection
2	VCC	P	Power Supply
3	VCC	P	Power Supply
4	NC	-	No connection
5	NC	-	No connection
6	NC	-	No connection
7	GND	P	Ground
8	Rxin0-	I	-LVDS Differential Data Input
9	Rxin0+	I	+LVDS Differential Data Input
10	GND	P	Ground
11	Rxin1-	I	-LVDS Differential Data Input
12	Rxin1+	I	+LVDS Differential Data Input
13	GND	P	Ground
14	Rxin2-	I	-LVDS Differential Data Input
15	Rxin2+	I	+LVDS Differential Data Input
16	GND	P	Ground
17	RxCLK-	I	-LVDS Differential Clock Input
18	RxCLK+	I	+LVDS Differential Clock Input
19	GND	P	Ground
20	Rxin3-	I	-LVDS Differential Data Input
21	Rxin3+	I	+LVDS Differential Data Input
22	GND	P	Ground
23	NC	-	No connection
24	NC	-	No connection
25	GND	P	Ground
26	NC	-	No connection
27	NC	-	No connection
28	NC	-	No connection
29	NC	-	No connection
30	GND	P	Ground
31	NC	-	No connection


32	NC	-	No connection
33	NC	-	No connection
34	NC	-	No connection
35	VGL	P	Gate OFF Voltage
36	NC	-	No connection
37	NC	-	No connection
38	VGH	P	Gate ON Voltage
39	NC	-	No connection
40	NC	-	No connection

PCAP PIN Definition

Pin	Symbol	Function
1	SDA	I2C data input and output
2	SCL	I2C clock input
3	RST	External Reset, Low is active
4	INT	External interrupt to the host
5	VDDT	Power Supply : +3.3V
6	VSS	Ground for analog circuit

Contour Drawing





Absolute Maximum Ratings

Item	Symbol	Min	Typ	Max	Unit
Operating Temperature	TOP	-20	—	+70	°C
Storage Temperature	TST	-30	—	+80	°C

Electrical Characteristics

Typical Operation Conditions

Item	Symbol	Values			Unit
		Min.	Typ.	MAX.	
Power voltage	VCC	3.0	3.3	3.5	V
	VGH	17.5	18	18.5	V
	VGL	-11.5	-10.5	-10.0	V
	VSP	—	5.5	—	V
	VSN	—	-5.5	—	V
Supply Voltage For Touch Logic	VDDT	2.8	—	3.3	V

Current Consumption

7.3. Item	Symbol	Values			Unit
		Min.	Typ.	MAX.	
Current for Driver	IGH	—	7.7	—	mA
	IGL	—	7.7	—	mA
	IVCC	—	85	130	mA