



REV.	DESCRIPTION	DRAWN	CHECKED	APPROVED
A	NEW RELEASE	YCH 09/06/10'		

NOTES:

1. SPECIFICATIONS:

- 1.0 CONTACT RESISTANCE: 30mΩ(max.) INITIAL FOR VBUS AND GND CONTACTS. 50mΩ(max.) INITIAL FOR ALL OTHER CONTACTS.
- 1.1 INSULATOR RESISTANCE: 100MΩ min. AT 100V DC.
- 1.2 CURRENT RATING: 1.8A FOR VBUS PIN AND ITS CORESPONDING GND PIN. 0.25A (MIN.) FOR ALL OTHER CONTACTS
- 1.3 VOLTAGE RATING: 30V AC/DC.
- 1.4 DIELECTRIC STRENGTH: AC 100V FOR 1 Minute.
- 1.5 OPERATING TEMPERATURE: -40°C ~ +105°C.

2. MATERIALS:

- 2.0 HOUSING: THERMOPLASTIC (UL 94-0).
- 2.1 CONTACT: COPPER ALLOY
- 2.2 SHELL: COPPER ALLOY.

3. PRODUCT NUMBER CODE:

DS1109 - X X X

- Contact plating
- 0: selective gold flash
- C 3u" gold
- 3: 30u" gold

- Shell plating
- 6: tin
- N: nickel
- 8: full gold

- Color of housing
- W: white
- B: black
- L: Blue

Tel:86-574-63508787
Fax:86-574-63510017
E-mail:sale@zhcnin.com.cn
Http://www.connfly.com

GENERAL TOLERANCE		ANGLE TOLERANCE		PROJECTION		TITLE		
X. ±0.60		X. ±5°		UNITS	mm	USB 3.0 B TYPE		
.X ±0.38		.X ±3°		SHEET SIZE	A4	SERIES	DS1109	
.XX ±0.25		.XX ±2°						
DRAWING TYPE		CUSTOMER		 晨翔电子有限公司 CONNFLY CONNFLY ELECTRONIC CO. LTD				
SCALE		1:1	SHEET					1 OF 1
DRAWING NO.		C-DS1109-XXX						



晨翔电子有限公司
CONNFLY CONNFLY ELECTRONIC CO. LTD