



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,
Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

Approval Sheet For Product Specification

Issued Date: 7/21/2005 (REV. NO: 1)

Product Name: SMD 6.0x3.5 20MHz Crystal Unit

TST Parts No.: TZ0650A

Customer Parts No. : _____

Company: _____

Division: _____

Approved by: _____

Date: _____

Checked by: _____ Kelly Huang

Approval by: _____ TF Yang

Date: _____ 7/21/2005



TAI-SAW TECHNOLOGY CO., LTD.

No. 3, Industrial 2nd Rd., Ping-Chen Industrial District,

Taoyuan, 324, Taiwan, R.O.C.

TEL: 886-3-4690038 FAX: 886-3-4697532

E-mail: tstsales@mail.taisaw.com Web: www.taisaw.com

SMD 6.0x3.5 20MHz Crystal Unit

MODEL NO.: TZ0650A

REV. NO.: 1

Features:

- Surface Mount Seam Weld Package
- Excellent Reliability Performance
- Good Frequency Perturbation and Stability over temperature

RoHS Compliant
Lead free
Lead-free soldering

Description and Applications:

Surface mount 6.0mmx3.5mm crystal resonator for use in wireless communications devices


Electrical Specifications:

TZ0650A	Specification
Nominal Frequency	20.000000 MHz
Mode of Oscillation	Parallel Resonance, Fundamental Mode
Operating Temperature Range	-35°C to +85°C
Frequency Stability over Operating Temperature Range	+/-15 ppm (referred to the value at 25°C)
Frequency Perturbations ¹	+/-0.25 ppm
Frequency Make Tolerance (FL)	+/-10 ppm @ 25°C +/- 3°C
Load Capacitance (CL)	8 pF
Equivalent Series Resistance (ESR)	35 Ω max
Drive Level	100 uW max.
Shunt Capacitance (Co)	2.0 pFmin
Motional Capacitance (C1)	8.0 +/- 3 fF
Marking	Laser marking

Note:

1. Peak to peak deviation from the frequency versus AT temperature curve fit. Minimum of 1 frequency reading every 2°C over operating temperature range. 100% testing and screening for frequency perturbations and micro jump occurrence.

Mechanical Dimensions (mm):




ITEM UNIT	A	B	C	D	E	F	G
M/M	3.50 ±0.13	6.00 ±0.13	1.00 ±0.16	1.50 ±0.13	0.9 REF.	3.00 ±0.13	1.4 REF.

Marking:

Line 1: Frequency (20.000)

Line 2: TST Logo + Crystal Product Code + Date Code




Product Code Table

Year	2001 2005	2002 2006	2003 2007	2004 2008
Product Code	Z	z	<u>Z</u>	<u>z</u>


Date Code Table

WK01	WK02	WK03	WK04	WK05	WK06	WK07	WK08	WK09	WK10	WK11	WK12	WK13
A	B	C	D	E	F	G	H	I	J	K	L	M
WK14	WK15	WK16	WK17	WK18	WK19	WK20	WK21	WK22	WK23	WK24	WK25	WK26
N	O	P	Q	R	S	T	U	V	W	X	Y	Z
WK27	WK28	WK29	WK30	WK31	WK32	WK33	WK34	WK35	WK36	WK37	WK38	WK39
a	b	c	d	e	f	g	h	i	j	k	l	m
WK40	WK41	WK42	WK43	WK44	WK45	WK46	WK47	WK48	WK49	WK50	WK51	WK52
n	o	p	q	r	s	t	u	v	w	x	y	z

Reel Dimensions (mm):



Tape Dimensions (mm):



[NOTE]:

1. Unless otherwise specified tolerance on dimension ± 0.1 mm.
2. Material: conductive polystyrene with color black.
3. 10 pitch cumulative tolerance ± 0.2 mm.

Reflow Profile:

