



**9NM60****Power MOSFET****9A, 600V N-CHANNEL
SUPER-JUNCTION MOSFET****DESCRIPTION**

The **UTC 9NM60** is a Super Junction MOSFET Structure and is designed to have better characteristics, such as fast switching time, low gate charge, low on-state resistance and a high rugged avalanche characteristics. This power MOSFET is usually used at DC-DC converters for power applications.

FEATURES

- * $R_{DS(ON)} \leq 0.56 \Omega @ V_{GS}=10V, I_D=4.5A$
- * By using Super Junction Structure
- * Fast Switching
- * With 100% Avalanche Tested


SYMBOL**ORDERING INFORMATION**

Ordering Number		Package	Pin Assignment			Packing
Lead Free	Halogen Free		1	2	3	
9NM60L-TA3-T	9NM60G-TA3-T	TO-220	G	D	S	Tube
9NM60L-TF3-T	9NM60G-TF3-T	TO-220F	G	D	S	Tube
9NM60L-TF1-T	9NM60G-TF1-T	TO-220F1	G	D	S	Tube
9NM60L-TF2-T	9NM60G-TF2-T	TO-220F2	G	D	S	Tube
9NM60L-TW1-T	9NM60G-TW1-T	TO-220WF	G	D	S	Tube
9NM60L-TM3-T	9NM60G-TM3-T	TO-251	G	D	S	Tube
9NM60L-TN3-R	9NM60G-TN3-R	TO-252	G	D	S	Tape Reel
9NM60L-TQ2-T	9NM60G-TQ2-T	TO-263	G	D	S	Tube
9NM60L-TQ2-R	9NM60G-TQ2-R	TO-263	G	D	S	Tape Reel

Note: Pin Assignment: G: Gate D: Drain S: Source

9NM60G-TA3-T (1) Packing Type (2) Package Type (3) Green Package	(1) T: Tube, R: Tape Reel (2) TA3: TO-220, TF3: TO-220F, TF1: TO-220F1, TF2: TO-220F2, TW1: TO-220WF, TM3: TO-251 TN3: TO-252, TQ2: TO-263 (3) G: Halogen Free and Lead Free, L: Lead Free
--	---

■ MARKING



■ **ABSOLUTE MAXIMUM RATINGS** ($T_C=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	RATINGS	UNIT
Drain-Source Voltage		V_{DSS}	600	V
Gate-Source Voltage		V_{GSS}	± 30	V
Drain Current	Continuous	I_D	9	A
	Pulsed (Note 2)	I_{DM}	18	A
Avalanche Current		I_{AR}	2.2	A
Avalanche Energy	Single Pulsed (Note 3)	E_{AS}	323	mJ
Peak Diode Recovery dv/dt (Note 4)		dv/dt	6	V/ns
Power Dissipation	TO-220/TO-220WF TO-263	P_D	82	W
	TO-220F/TO-220F1 TO-220F2		30	W
	TO-251/TO-252		58	W
Junction Temperature		T_J	+150	$^{\circ}\text{C}$
Storage Temperature		T_{STG}	-55 ~ +150	$^{\circ}\text{C}$

Notes: 1. Absolute maximum ratings are those values beyond which the device could be permanently damaged.

Absolute maximum ratings are stress ratings only and functional device operation is not implied.

2. Repetitive Rating: Pulse width limited by maximum junction temperature.

3. $L=100\text{mH}$, $I_{AS}=2.54\text{A}$, $V_{DD}=50\text{V}$, $R_G=25\Omega$, Starting $T_J=25^{\circ}\text{C}$

4. $I_{SD} \leq 9.0\text{A}$, $di/dt \leq 200\text{A}/\mu\text{s}$, $V_{DD} \leq BV_{DSS}$, Starting $T_J=25^{\circ}\text{C}$

■ **THERMAL DATA**

PARAMETER		SYMBOL	RATINGS	UNIT
Junction to Ambient	TO-220/TO-220F TO-220F1/TO-220F2 TO-220WF/TO-263	θ_{JA}	62.5	$^{\circ}\text{C}/\text{W}$
	TO-251/TO-252		110	$^{\circ}\text{C}/\text{W}$
	TO-220/TO-220WF TO-263		1.52	$^{\circ}\text{C}/\text{W}$
	TO-220F/TO-220F1 TO-220F2		4.16	$^{\circ}\text{C}/\text{W}$
Junction to Case	TO-251/TO-252	θ_{JC}	2.15 (Note)	$^{\circ}\text{C}/\text{W}$

Note: Device mounted on FR-4 substrate PC board, 2oz copper, with 1inch square copper plate.


■ **ELECTRICAL CHARACTERISTICS** ($T_J=25^{\circ}\text{C}$, unless otherwise specified)

PARAMETER		SYMBOL	TEST CONDITIONS	MIN	TYP	MAX	UNIT
OFF CHARACTERISTICS							
Drain-Source Breakdown Voltage		BV _{DSS}	I _D =250μA, V _{GS} =0V	600			V
Drain-Source Leakage Current		I _{DSS}	V _{DS} =600V, V _{GS} =0V			10	μA
Gate- Source Leakage Current	Forward	I _{GSS}	V _{GS} =30V			100	nA
	Reverse		V _{GS} =-30V			-100	nA
ON CHARACTERISTICS							
Gate Threshold Voltage		V _{GS(TH)}	V _{DS} =V _{GS} , I _D =250μA	2.5		4.5	V
Static Drain-Source On-State Resistance		R _{DS(ON)}	V _{GS} =10V, I _D =4.5A			0.56	Ω
DYNAMIC PARAMETERS							
Input Capacitance		C _{ISS}	V _{DS} =25V, V _{GS} =0V, f=1.0MHz		590		pF
Output Capacitance		C _{OSS}			530		pF
Reverse Transfer Capacitance		C _{RSS}			57		pF
SWITCHING PARAMETERS							
Total Gate Charge (Note 1)		Q _G	V _{DS} =480V, V _{GS} =10V, I _D =9A , I _G =1mA (Note 1, 2)		24		nC
Gate to Source Charge		Q _{GS}			5.2		nC
Gate to Drain Charge		Q _{GD}			18.2		nC
Turn-ON Delay Time (Note 1)		t _{D(ON)}	V _{DD} =100V, V _{GS} =10V, I _D =9A, R _G =25Ω (Note 1, 2)		8.8		ns
Rise Time		t _R			24		ns
Turn-OFF Delay Time		t _{D(OFF)}			64		ns
Fall-Time		t _F			33.5		ns
SOURCE- DRAIN DIODE RATINGS AND CHARACTERISTICS							
Maximum Body-Diode Continuous Current		I _S				9	A
Maximum Body-Diode Pulsed Current		I _{SM}				18	A
Drain-Source Diode Forward Voltage (Note 1)		V _{SD}	I _S =9.0A, V _{GS} =0V			1.4	V
Reverse Recovery Time (Note 1)		t _{rr}	I _S =9.0A, V _{GS} =0V,		310		ns
Reverse Recovery Charge		Q _{rr}	dI _F /dt=100A/μs		7.83		μC


Notes: 1. Pulse Test: Pulse width $\leq 300\mu\text{s}$, Duty cycle $\leq 2\%$.

2. Essentially independent of operating temperature.

■ TEST CIRCUITS AND WAVEFORMS




Peak Diode Recovery dv/dt Test Circuit




Peak Diode Recovery dv/dt Waveforms


■ TEST CIRCUITS AND WAVEFORMS




Switching Test Circuit




Switching Waveforms




Gate Charge Test Circuit



Gate Charge Waveform









Unclamped Inductive Switching Test Circuit









Unclamped Inductive Switching Waveforms


TYPICAL CHARACTERISTICS



TYPICAL CHARACTERISTICS (Cont.)



TYPICAL CHARACTERISTICS (Cont.)



UTC assumes no responsibility for equipment failures that result from using products at values that exceed, even momentarily, rated values (such as maximum ratings, operating condition ranges, or other parameters) listed in products specifications of any and all UTC products described or contained herein. UTC products are not designed for use in life support appliances, devices or systems where malfunction of these products can be reasonably expected to result in personal injury. Reproduction in whole or in part is prohibited without the prior written consent of the copyright owner. UTC reserves the right to make changes to information published in this document, including without limitation specifications and product descriptions, at any time and without notice. This document supersedes and replaces all information supplied prior to the publication hereof.